

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>45</u> N. S., R. <u>22</u> E. W.	<u>A-3, A-4, B-3</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, David B. Babbitt do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on October 31 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- A-3 N.W. section corner - Section 7; Wood Post, Y. Birch 10 - N30°E - 33 lks.; Sugar 13 - S20°E - 42 lks.; Fir 8 - N53°W - 27 lks.; Fir 9 - N54°W - 26 lks.; Sugar 12 - S60°W - 44 lks.
 - A-4 West 1/4 corner - Section 7; Wood Post, Cedar 12 - S69°E - 10 lks.; Do. 5 - N12°W - 13 lks.
 - B-3 North 1/4 corner - Section 7; Wood Post, Y. Birch 12 - N48°W - 20 lks.; Sugar 10 - S40°E - 20 lks.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- A-3 Set by double proportion using section corners one mile north and one mile south, 1/4 corner 1/2 mile east and a very definite stream call 39.90 west. This method causes the corner to fall 30.4' in front of the blaze on a very old 18" hemlock register tree and will cause the 1/4 corner position 1/2 mile north to fit an existing old fence corner much better than using a straight line north and south for two miles. Therefore, I believe this method comes closer to re-establishing this corner in its original position than a straight line method would.
- A-4 Set M.P.O.L. between the N.W. and S.W. corners of Section 7.
- B-3 Set from stump of N.W. O.B.T. (y. birch N.W.) very definite old scars but no scribe marks visible at this time. Measurements and bearings east and west are good.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- ALL 1" pipe, 4" aluminum cap.
- A-3 6" Maple - N69°W - 6.3'; Old Register Tree 18" Hemlock - S61°W - 30.4'; 7" Hemlock - N90°E - 94.7'; 12" Maple - N82°E - 31.3'.
 - A-4 12" Cedar - N69°W - 28.7'; 4" B. Ash - S22°E - 15.6'; 4" Cedar - N63°E - 28.2'; 10" Cedar N13°E - 34.0'.
 - B-3 8" B. Cherry - S56°W - 13.1'; 5" R. Maple - N70°W - 13.8'; 16" Hemlock - N14°W - 52.8'; 12" H. Maple - N77°E - 5.9'.

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY David B. Babbitt CHIEF OF SURVEY PARTY DATE 1-26-81
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 21558