LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in			
Grand Traverse (County)	Located In:	Corner Code #	
1. Public Land Survey	T <u>27N</u> R <u>9W</u> TR	<u>F7</u>	
2. Property Controlling in Section3. Miscellaneous Property in Sec.	S TR S TR S TR		Register of Deeds Stamp & File Numb
4. Lot No , Reco	rded Plat		A B C D E F G H I J K L M
5. Private Claims		 	1 2 - 6 - 5 - 4 - 3 - 2 - 1
I, <u>Craig W. McVean</u> , in a field survey on <u>May 4</u> , 19 <u>99</u> do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the comer points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:			3 4 7 - 8 9 - 10 - 11 - 12 - 5 6 - 18 - 17 - 16151413 - 7 8 - 19 - 20 - 21 - 22 - 23 - 24 - 9
NOTE: Not more than 2 c this certificate.	orners, all in the same town an	d range, may be recorded on	10 30 29 28 27 26 25 11 12 31 32 33 34 35 36
F-7 -1850- GLO, L.Lyon, SHemlock 16" S37 Sugar 18" N23 -1915 – L.2, pg. 498 - Found point of old workstake plain with axe more consumers Power Power Power Consumers Power Power Power Power Power Power Power Power Power Pow	"E 34 links 3"W 33 links CSR; E.P.Waterman - set iron poden stake from remains in stone tarks, corner is 7' N. of straight linc. — 1967 — P.Perla 1" iron found 4" W. Pine S47°01'W 29.6	ipe with stones around. pile stump of US witnesses (su le corner #10 to #18 (Sec.21) 15' pe 17 29.63' S43°W 11.74' N35°E	g. 18" N°23W 33 L) – point of
B. Description of corner evid	ence found and/or method applie	ed in restoring or reestablishing o	corner:
of line between E-7 to	section 16 & 21- Found 1" I.D. X G-7. CL. of N-S bit Rd is 104 +/- and faithful perpetuation of the p	W. C/L of E-W 2 tracks is 10' +/	nes. Pipe calculates 5.01' N (EPW-7'N) - S. Iron pipe by Waterman is
C. Description of monument	for corner and accessories estab	olished to perpetuate locating the	e position of the comer:
East 1.0' to an N5°E 5.24' to fnd S81°E 26.88' to fnd N58°W 33.25' to fnd	Orange Carsonite Post . nail in E_side 25" Sugar Map	ole (CPC,RM,JG)	galvanized iron pipe in ring of stones. OF MICAGO CRAIG W. McVEAN PROFESSIONAL SURVEYOR No. 39088
Signed by Mire	M. Malla	non /	2/13/1999 3008
Surveyor's Michigan License	No. <u>39088</u>		ESSIONA