

97380

RECORDED
HILLSDALE CO. MICH.

'94 NOV 28 AM 11 07

ACCEPTED BY THE HILLSDALE COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT MEETING HELD ON 11-28-94
AL RINGENBERG, CO. REP.

REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Judy Namjardt
REG. OF DEEDS

For corners in

Hillsdale
(County)

Located In:

Corner Code #

1. Public Land Survey

T 6S R 2W

F-13

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

SURVEY &
REMONUMENTATION

APR 27 1995

Register of Deeds Stamp & File Number
COMMISSION

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Frederick J. Cutcher, in a field survey on November 18, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
Survey #934, Oct. 5, 1882, George Mark, County Surveyor: Stake & stone: Hickory 8" N. 40° E., 3 3/8 links.

Records of A.E. Ringenberg: T. Clow, Feb. 9, 1984: Found stone from George Mark's witness and referenced: West, 35.9', S.W. corner concrete fence post; N. 40° W., 4.57', P.K. W. side 4" Sassafras; N. 78° E., 4.82' P.K. S. side 4" Sassafras; N. 80° E., 63.10', P.K. S. side 28" Hickory; South, 4.25', P.K. W. side 4" Sassafras.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found stone at ground surface. Agrees with references. Replaced stone with 3/4"x36" County remonumentation rod and is accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4"x36" County remonumentation bar
In line with fenceline to the East.
S.E. corner concrete post West, 35.8'
Found P.K. nail in W. side 6" Sassafras N. 20° W., 4.48'
Found P.K. nail in W. side 6" Sassafras South, 4.30'
Found P.K. nail in N.W. side 6" Sassafras N. 78° E., 4.78'
Nail S. side 28" Hickory N. 80° E., 63.10'



Signed by Frederick J. Cutcher
24592

Date November 23, 1994

Surveyor's Michigan License No. _____