

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF --	(IRON COUNTY) LOCATED IN --	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. _____ S., R. _____ E. _____ W. _____	_____
2. PROPERTY CONTROLLING IN SECTION	12 T. 45 N. <input checked="" type="checkbox"/> S., R. 31 <input checked="" type="checkbox"/> E. _____ W. _____	10, 16
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ S., R. _____ E. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August 8, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

**Corner 10: Not set on original survey nor subsequently, apparently.**

**Corner 16: Not set on original survey nor subsequently, apparently.**

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

**Corner 10: Established on line between section corner 20.0135 chains south and 1/4 corner 20.0135 north.**

**Corner 16: Established on line between section corner 19.9885 chains east and 1/4 corner 19.9885 chains west.**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**Corner 10: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.**  
 8" Cherry N84°E 84.4 ft., 1/16S, BT  
 7" Elm S 6°E 75.6 ft., 1/16S, BT

**Corner 16: Set 1" I.D. x 36" iron pipe with 4" aluminum cap.**  
 6" Maple S51°W 43.4 ft., 1/16S, BT  
 4" Maple N42°E 12.2 ft., 1/16S, BT

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Keith L. Sackett DATE 10-27-81

CHIEF OF SURVEY PARTY  
 MICHIGAN REGISTERED LAND SURVEYOR  
**Keith L. Sackett**  
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

