

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Kalkaska
(County)

Located In

Corner Code #

1. Public Land Survey	T _____	R _____	_____
2. Property Controlling in Section	T _____	R _____	_____
	S 24	T 25N	R 7W 11
	S 24	T 25N	R 7W CSSW 1/64
3. Miscellaneous Property in Section	S _____	T _____	R _____
	S _____	T _____	R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on March 15, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3		2	1					
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

11 - None

CSSW 1/64 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

11 - SW 1/16 Cor. Sec. 24 - Set 2" Alum. Cap on 5/8" x 34" iron rebar per standard BLM procedure.

CSSW 1/64 - being the SW Cor. of the N 1/2 of SE 1/4 of SW 1/4, Sec. 24 - Set 2" Alum. Cap on 5/8" x 34" iron rebar Per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

11 - Stamped 2" Alum. Cap on 5/8" x 34" iron rebar Set blue carbonite post w/ loc tag 1' NE

West 11.48' to set N & T in S. side 10" R. Maple
N20°W 12.63' to set N & T in SW side 6" Cedar
S54°E 4.59' to set N & T in NE side 12" R. Maple
S11°E 11.13' to set N & T in E. side Tw. 12" Cedar
N48°E 24.28' to set N & T in side 8" Cedar

CSSW 1/64 - Stamped 2" Alum. Cap on 5/8" x 34" iron rebar Set blue carbonite post w/ loc tag 1' SE
S36°W 9.99' to set N & T in NW side 22" R. Pine
N86°E 19.42' to set N & T in N. side 6" R. Pine
N22°E 10.14' to set N & T in W. side 19" R. Pine
N42°W 9.05' to set N & T in SW side 9" R. Pine

Signed by:

Craig W. McVean

Date:

8/3/2004

Surveyor's Michigan License No.: 39088