

SURVEY &  
REMONUMENTATION

\$7.00  
\$2.00

DEC 08 1999

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

SECTION

For corners in

Kent  
(County)

Located in: Grattan  
Township

Corner Code #

1. Public Land Survey T 8N R 9W D-5W  
T R  
T R Witness Monument  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat  
5. Private Claims

I, Randy Kolehouse, in a field survey on March 24 19 98,  
do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the interior, Bureau of  
Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3,  
4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a  
Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered,  
found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-5 This corner was not originally set by the G.L.O.

1972 Cert. Survey L. 1 P. 50 Moore & Bruggink  
1993 L.C.R.C. #6776 T. Starr  
1994 L.C.R.C. #8001 Glaza & Associates

Iron  
Fnd. Iron / Set K.C. Witness Monument  
K.C. Witness Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Tom Starr on  
3/15/93 and was recorded per L.C.R.C. #6776.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-5 Found a Standard Kent County Witness Monument on the West side of Toohey Lake on line of a tree row running East and  
West and 1.0' South of a fence line running East and West per L.C.R.C.'s #6776 and #8001 as set by Tom Starr in place of  
an iron he found which checked a 1972 survey by Moore & Bruggink.

L.C.R.C. #6676

Nail & Tag in S. side 30" Oak N 72° W 9.66'  
Nail & Tag in W. side 10" Oak N 32° W 3.35'  
Nail & Tag in E. side 12" Maple N 54° E 3.45'  
Nail & Tag in N. side 10" Maple S 88° E 10.85'  
Nail & Tag in E. side 12" Triple Maple S 40° E 29.65'  
Nail & Tag in E. side 10" Quad. Beech S 05° E 4.83'

L.C.R.C. #8001

Nail & K.C. remon tag in S side 30" Oak N 72° W 9.62' (m. 9.61')  
Nail & K.C. remon tag in W side 10" Oak N 32° W 3.28' (m. 3.29')  
Nail & K.C. remon tag in E side 12" Maple (stump) N 54° E 3.41' (m. 3.42')  
Nail & K.C. remon tag in N side 12" Maple S 88° E 11.01' (m. 11.07')  
Nail & K.C. remon tag in E side 10" Triple Maple S 40° E 29.70 (m. 29.68')  
Nail & K.C. remon tag in E side 14" Quad. Beech S 05° E 4.87' (m. 4.88')

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence  
of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-5 Standard Kent County Witness Monument

Nail & K.C. remon. tag on S side 30" Oak N 72° W 9.61'  
Nail & K.C. remon. tag on W side 10" Oak N 32° W 3.29'  
Nail & K.C. remon. tag on E side 12" Oak (stump) N 54° E 3.42'  
Nail & K.C. remon. tag on N side 12" Maple S 88° E 11.07'  
Nail & K.C. remon. tag on E side 10" Triple Maple S 40° E 29.68'  
Nail & K.C. remon. tag on E side 4" Quad. Beech S 05° E 4.88'

On tree row running E-W  
Fence line running E-W, North 1.0'

Signed by Randy J. Kolehouse

EARTH TECH

Date 9-1-98

Surveyor's Michigan License No. 25854

