

MAY 22 2000

SECTION

Seg. 2
"Other
Code #4LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)Located in: Courtland
Township

Corner Code #

1. Public Land Survey T 9N R 10W G-10E
 T _____ R _____
 T _____ R _____
 T _____ R _____
 2. Property Controlling S _____ T _____ R _____ 2201.54 East
 in Section S _____ T _____ R _____ Of G-10
 3. Miscellaneous S _____ T _____ R _____
 Property in Sec. S _____ T _____ R _____
 4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

REG. OF DEEDS

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

1999 OCT 15 AM 8:05

11327
Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2							1
3												
4	7	6	5	4	3	10	11	12				
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	10	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Randy Kolehouse, in a field survey on January 28 1999, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-10 1837 1919-1976 1994	G.L.O. Notes Survey Notes L.C.R.C. #6965	Cathcart Williams & Works William R. Byl	Set Post Iron Fnd. Iron / Set K.C. Witness Monument
--------------------------------	--	--	---

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by William R. Byl on 2/18/99 and was recorded per L.C.R.C. #6965.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-10 Found a Standard Kent County Witness Monument 12' + West of the C/L of Hessler Drive (bit.) running North and South per L.C.R.C. #6965 as set by William Byl in place of a iron used in various surveys by Williams & Works.

L.C.R.C. #6965

NE cor. fndn. hse. #7502 S 40°W 67.70' (m. 67.73')
 Nail & KC Remon. tag S. side 30" Oak S 80°W 27.51' (m. 27.53')
 Nail & KC Remon. tag E. side 36" Oak N 10°W 16.22' (m. 16.13')
 Nail & KC Remon. tag S. side 30" Oak S 75°E 43.59' (m. 43.64')
 Nail & KC Remon. tag E. side Power Pole S 45°E 55.40' (m. 55.47')

P.A. 345 1990 KENT COUNTY

PEER APPROVED 2/25/99

CHAIRMAN

Harry Huber

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10 Standard Kent County Witness Monument

NE cor. conc. fndn. hse. #7502 S 40° W 67.73'
 Nail & K.C. remon. tag on S side 30" Oak S 80° W 27.53'
 Nail & K.C. remon. tag on E side 36" Oak N 10° W 16.13'
 Nail & K.C. remon. tag on S side 30" Oak S 75° E 43.64'
 Nail & K.C. remon. tag on E side P. pole S 45° E 55.47'
 C/L of bit. road running N-S, East 12'

Signed by

Randy J. Kolehouse

WILLIAMS & WORKS

Surveyor's Michigan License No. 25854