

SURVEY & REMONUMENTATION

FEB 18 1994

LIBER

1 PG 1075

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in PAVILION TWP.

KALAMAZOO
(County)

Located In:

Corner Code #

- | | | | | | |
|------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 3S | R | 10W | A-5 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | R | |
| | S | | T | R | |
| 3. Miscellaneous | S | | T | R | |
| Property in Sec. | S | | T | R | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Allen H. McMachen a field survey on December 4, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1888 - F. Hodgeman C.S. placed Clay Tile post during official Township Remonumentation.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Clay Tile at surface of existing ground.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found Clay Tile is accepted as a careful and faithful perpetuation of the original corner. Placed Standard Sleeve and monument box over existing Tile, accessories:

Nail & Tab in North face	12" Oak S. 80 deg. W. 55.77'
Nail & Tab in East face	16" Oak S. 35 deg. W. 51.89'
Nail & Tab in East face	12" Oak S. 06 deg. W. 21.22'
Nail & Tab in South face	7" Elm S. 62 deg. E. 30.84'

**RATIFIED
BY KALAMAZOO COUNTY
REMONUMENTATION
PEER GROUP
12-16-93**



Signed by Allen H. McMachen
Surveyor's Michigan License No. 16935

Date 1/19/94