

SURVEY & REMONUMENTATION

MECOSTA COUNTY REMONUMENTATION PROGRAM

SEP 12 1996

CORNER APPROVED BY PEER GROUP ON April 15, 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF MECOSTA
RECEIVED FOR RECORD

For corners in Mecosta Located In: _____ Corner Code # _____
(County)

1. Public Land Survey Sec. 34 T 14N R 10W H-11
 T _____ R _____
 T _____ R _____
 T _____ R _____

2. Property Controlling in Section S _____ T _____ R _____
 S _____ T _____ R _____

3. Miscellaneous Property in Sec. S _____ T _____ R _____
 S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

'96 AUG 21 A10:32

J. Brown
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, James J. Keller, in a field survey on Jan. 30 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- Feb. 25, 1838, Abner E. VanNess "Set Qr. Sec. Post"
10" Hemlock N48°W 18 Links
12" Sugar S30°E 9 Links
- Nov. 3, 1975, Douglas W. Hooth #7966 MDOT "Found Old Post & Stone in Fnc Cor. Set 3/4" I.D. Iron Pipe 32" Long"
14" Maple S10°E 8.19'
18" Maple S82°W 31.56'
8" Birch N72°E 32.95'
- Jan. 30, 1993, James J. Keller #10693, "Found 3/4" Iron in Fnc Cor. Fits 1975 Witness by D. Hooth #7966"
Set 30d 4" White Birch N47°W 17.55'
Set 30d and Found MSED Tag 10" White Birch N83°E 32.95'
Set 30d and Found MSED Tag 16" Maple S20°E 8.20'
Set 30d 18" Beech S81°W 30.81'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

February 1, 1996 James J. Keller #10693 "Found 3/4" Iron 4" High in N-S Fence matching 1993 witness."
 Found nail North East side 6" White Birch N46°W 17.57'
 Found nail North side 8" White Birch N85°E 32.93'
 Set nail West side 20" Maple S18°E 8.06'
 Found nail North side 24" Maple S80°W 30.80'

APPROVED BY MECOSTA CO. PEER GROUP
IN ACCORDANCE WITH P.A. 343 of 1990

James G. Knapp
CHAIRMAN
DATE April 15, 1996

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Remonumentation Monument and is accepted as careful perpetuation of the location of the Original Monument.
 Set 60d and tag North East side 6" White Birch N49°W 17.62'
 Set 60d and tag North side 8" White Birch N83°E 32.95'
 Set 60d and tag West side 20" Maple S17°E 8.06'
 Set 60d and tag North side 24" Maple S79°W 30.83'

Signed by *James J. Keller* Date July 1, 1996
 Surveyor's Michigan License No. 10693



