

JAN 31 2001

LIBER 3124 PAGE 911

STATE OF MICHIGAN  
COUNTY OF MUSKEGON  
RECEIVED FOR RECORD

200 DEC 29 AM 11: 22

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

*Mark Fairchild*  
REGISTER OF DEEDS

For corners in

Muskegon

(County)

Located In:

Corner Code #

1. Public Land Survey

T 9N R 14W B-11

T R

T R

T R

2. Property Controlling in Section

S T R

S T R

3. Miscellaneous Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Ralph W VanRiper, in a field survey on Dec. 7, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

1837 GLO Set, Quarter Section Post between Sections 30 & 31 : Beach 10" N76°W 28L  
Hemlock 6" S72°E 5L

Late 1920's MCRC Set corner on Fence Line E & N & S 1/4 Line as shown by a Farmer

1975 C F Lewandoski found 1" Iron Pipe : WSW 36.85' 12" Poplar : WNW 51.96' 15" Twin B1. Oak  
NNE 44.43' 8" Poplar

Westshore found Capped Iron "All Points # 17639" : N 72° W 51.81' Twin 18" B Oak:  
S 40° W 13.10' 6" Poplar : N 15° W 56.31' 10 Poplar

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" Capped Rod "All Points # 17689" Over 1" Pipe (No Occupations Lines at Corner)

Historical usage, documentation and evidence of corner location reviewed and ratified by Muskegon County Peer Group 8/11/2000

POSITION OF SAID  
RECORDED CORNER  
REVIEWED & RATIFIED  
BY MUSKEGON COUNTY  
PEER GROUP IN ACCORDANCE  
WITH P.A. 345, OF 1990  
*RWR*  
*8/11/00*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 2 3/4" Cast Iron "County Survey" Monument

S 11° E 13.54' 7" Poplar, Found Spike in E side  
S 40° W 13.13' 10" Poplar, Found Spike in W side  
S 85° W 24.65' 6" Poplar, Set Spike in N side  
S 68° W 51.84' Tw 18" Oak, Found Spike in Sly side  
N 23° W 30.44' 5" Poplar, Set Spike in Sly side  
N 22° E 24.23' 3" Poplar, Set Spike in E side



Signed by Ralph W. Van Riper  
Surveyor's Michigan License No. 16946

Date 12/26/00