

DEC 27 1993

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

#906
LIBER 283 PAGE 432

For corners in

Missaukee
(County)

Located In:

Corner Code #

1. Public Land Survey

T 21N R 8W

I-13

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

MISSAUKEE COUNTY MICHIGAN

RECORDED DEC 16 1993 12:40 P.M.

Paulyn Flare
REGISTER

Register of Deeds Stamp & File Number

I, J. Dean Geers, in a field survey on December 13, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-13) 1837 GLO Section post by John Brink, Deputy Surveyor
Beech 18 N 43° W 23, Sugar 12 N 49° E 43

I-13) 1991 Wilcox Certificate of Survey, Liber S-3, page 57: Found railroad spike

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-13) Section corner common to Sections 34 and 35

Found railroad spike $\pm 2'$ Southerly of centerline of road East-West and $\pm 2'$ Westerly of
centerline of road Northerly. This corner is accepted as a careful and faithful perpetuation of
the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

I-13) Replaced found railroad spike with 1/2" x 36" Iron and Missaukee County monument in
monument box

N 34° W - 113.53 - Power pole
N 25° E - 95.39 - Power pole
N 65° E - 81.75 - Top center of telephone riser
S 01° E - 35.40 - Set 1/2" Iron and cap

Peer Group Reviewed and Approved

Date: 12-15-93

J. Dean Geers
J. Dean Geers, Missaukee Co. Representative

Signed by *J. Dean Geers*

Date 12/15/93

Surveyor's Michigan License No. 33977