



\*LC-110021\*

JERI WINTON  
OSCODA COUNTY

# LAND CORNER RECORDATION CERTIFICATE

REGISTER OF DEEDS

Filing Requirement of Act 74, Mich. PA 1970

07/07/2011

12:51:23PM

FEE:

\$14.00

PAGES: 1

RCPT#: 15316

LC-11002

CORNER RECORDATION

For Corners In:  
Oscoda Located In Corner Code #  
(County)

|                                      |   |            |       |           |            |
|--------------------------------------|---|------------|-------|-----------|------------|
| 1. Public Land Survey                | T | <u>28N</u> | R     | <u>2E</u> | <u>J-4</u> |
|                                      | T | _____      | _____ | _____     | _____      |
| 2. Property Controlling in Section   | S | _____      | T     | _____     | R          |
|                                      | S | _____      | T     | _____     | R          |
| 3. Miscellaneous Property in Section | S | _____      | T     | _____     | R          |
|                                      | S | _____      | T     | _____     | R          |

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Carl T. Kiiskila, in a field survey on June 4, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

|    |    |   |    |   |    |   |    |   |    |   |    |   |
|----|----|---|----|---|----|---|----|---|----|---|----|---|
| A  | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M |
| 1  |    |   |    |   |    |   |    |   |    |   |    |   |
| 2  | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   |
| 3  |    |   |    |   |    |   |    |   |    |   |    |   |
| 4  | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   |
| 5  |    |   |    |   |    |   |    |   |    |   |    |   |
| 6  | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   |
| 7  |    |   |    |   |    |   |    |   |    |   |    |   |
| 8  | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   |
| 9  |    |   |    |   |    |   |    |   |    |   |    |   |
| 10 | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   |
| 11 |    |   |    |   |    |   |    |   |    |   |    |   |
| 12 | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   |
| 13 |    |   |    |   |    |   |    |   |    |   |    |   |

A. Description of original monument and accessories and/or subsequent restoration:

J-4 This corner position was not established during the Original Government Survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

J-4 Set the center of section 11 at the intersection of the North-South and East-West quarter lines using K.J. Ostling's RLS#10068 1971 survey of section 11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-4 Set a 2" Aluminum Cap on a 5/8"x34" rerod  
Wit: N16°E 13.94' to set N&T on E side 5" Poplar  
N55°E 16.56' to set N&T on S side 6" Maple  
S30°E 16.06' to set N&T on W side 5" Maple  
N60°W 2.41' to set N&T on N side 4" Maple  
Set a Blue Carsonite Post North 1'±



Signed by: Carl T Kiiskila  
Surveyor's Michigan License No.: 33981

Date: 7-7-11