

**SURVEY & REMONUMENTATION**

**FILED**

**JAN 11 1999**

**DEC 28 4 35 PM '98**

**SECTION**

E/4 cor., Sec. 25

**LAND CORNER RECORDATION CERTIFICATE**

**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in VAN BUREN  
(County)

Located In:

Corner Code #

1. Public Land Survey	T	1S.	R	13W.	M-10
	T		R		
	T		R		
	T		R		
2. Property Controlling in Section	S		T	R	
	S		T	R	
3. Miscellaneous Property in Section	S		T	R	
	S		T	R	

*Mark A. Smith*  
VAN BUREN CO.  
REGISTERED COUNTY CLERK

7-00

3307 1128 0101 105URVEY

*LIBER 5 PAGE 201*

**Register of Deeds Stamp & File Number**

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Allen H. McMachen, in a field survey on December, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

- 1827 - William Brookfield, D.S., North on East boundary 40.00 chains (2640') and set post corner. 7" Black Ash S. 31° W. 27 lks. (17.82'), 16" Black Ash N. 47° 30' W. 40 lks. (26.40').
- 1901 - W.H. Goss, D. C.S., "Found stake & remains of one witness, set stake by old one-Alamo corner is 27.5 lks. (18.15') North.
- 1915 - W.H. Goss D.C.S., "Set 1 1/2" pipe, 4' long, 4" Elm S. 33° 30' W. 25.5', 4" Elm N. 30° 30' W. 76', distance South is 39.83 chains (2628.78') to SE corner.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

Found 1 1/2" iron pipe 14" below road surface. Found pipe was ratified by the Van Buren County Remonumentation Peer Group on June 24, 1998.

Ratified by Peer Group in accordance with P.A. 345 of 1990  
Van Buren County Surveyor  
Date D. R. A. 12-28-98

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Found 1 1/2" pipe is accepted as the best available evidence of the position of the original corner. Replaced found pipe with a standard Van Buren County Remonumentation Monument with monument box over, Accessories:

- Nail & Tab in 8" Twin Maple S. 10° E. 44.04'
- Nail & Tab in 6" Maple S. 70° E. 67.13'
- Nail & Tab in U. pole N. 50° W. 50.88'
- "X" in concrete headwall S. 70° W. 9.67'
- 4' South of centerline "EF" Avenue



Signed by Allen H. McMachen

Date 12/18/98

Surveyor's Michigan License No. 16935