

JAN 14 1998

VAN BUREN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

DEC 16 12 00 PM '97

SECTION

For corners in VAN BUREN COUNTY Located in: COLUMBIA TWP. W 1/4 COR. SEC18T1S,R15W Corner ID #

Mark A. Smith VAN BUREN CO SURVEYOR

- 1. Public Land Survey T. 1S R. 15W A6
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R
4. Lot No. Recorded Plat
5. Private Claims

Liber 5 PAGE 4b

Register of Deeds Stamp & File Number

Grid table with columns A-M and rows 2-13, containing numbers 1-36.

I, Alan Bartlett in a field survey on December 8 1997 hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

NOT SET IN ORIGINAL GOVERNMENT SURVEY
6/1972 LCRC LIBER 1 PAGE 458 MITCHELL
SET 1" IRON PIPE BY SINGLE PROPORTION BETWEEN A7 AND A3
WITNESSES
10" BIRCH N10°W 78.70'
8" APPLE S40°E 74.55'
CENTER ENTRANCE DRIVE TO EAST SOUTH 26.0'

6/1972 RECORDED SURVEY LIBER 002 PAGE 91 ALPHA ENGINEERING/MITCHELL
SHOWS: 7927.44' FROM N.W. CORNER SECTION 7 TO WEST 1/4 SECTION 18
2642.48' FROM WEST 1/4 TO SW CORNER SECTION 18
10,569.92/4=2642.48'

8/1973 RECORDED SURVEY LIBER 004 PAGE 76 ALPHA ENGINEERING/MITCHELL
WITNESSES
SAME AS ABOVE AND CENTER LINE OF COUNTY ROAD 681 EAST 4.0'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

SET AT HALFWAY DISTANCE BETWEEN A5 AND A7 COLUMBIA TWP. CORNERS APPROVED BY VAN BUREN COUNTY PEER GROUP. ESTABLISHED MONUMENT IS 2.51' SOUTH OF 1972 PRO-RATED LOCATION. (1/2 MILE DISTANCE FROM SW CORNER = 2639.85') THIS GOVERNMENT MONUMENT WAS RESTORED WITH APPROVAL OF THE VAN BUREN COUNTY REMONUMENTATION PEER GROUP OF SURVEYORS ON NOVEMBER 19 1997.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 2 1/2" HARRISON MONUMENT AND MONUMENT BOX 4' NORTH OF CENTERLINE DRIVE EAST, 25' NORTH OF CENTER LINE DRIVE WEST, AND 2' WEST OF CENTER LINE OF COUNTY ROAD 681.

WITNESSES
N77°E 40.88' 1" ANGLE IRON
S15°E 99.40' NAIL AND FLASHER IN 9" CEDAR
NORTH 25.59 E 1/4 CORNER OF SECTION 13 (HARRISON MONT. IN MONT. BOX)
N45°W 42.30' 1" IRON PIPE WITH CAP
S60°W 24.19' NAIL AND FLASHER IN 8" APPLE

THIS POSITION NOT ESTABLISHED BY ORIGINAL GOVERNMENT SURVEYORS. THIS MONUMENT IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE CORNER

Signed by Alan K. Bartlett Date 12/15/97
Surveyor's Michigan License No. 35988

Ratified by Peer Group in accordance with P.A. 345 of 1998 Van Buren County Surveyor

Date D. R. G. 12/16/97

