

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:  
Wexford Located In \_\_\_\_\_ Corner Code # \_\_\_\_\_  
 (County)

- |                                      |             |              |              |          |
|--------------------------------------|-------------|--------------|--------------|----------|
| 1. Public Land Survey                | T _____     | R _____      |              |          |
|                                      | T _____     | R _____      |              |          |
| 2. Property Controlling in Section   | S <u>33</u> | T <u>24N</u> | R <u>11W</u> | <u>6</u> |
|                                      | S <u>33</u> | T <u>24N</u> | R <u>11W</u> | <u>7</u> |
| 3. Miscellaneous Property in Section | S _____     | T _____      | R _____      |          |
|                                      | S _____     | T _____      | R _____      |          |

4. Lot No: \_\_\_\_\_ Recorded Plat: \_\_\_\_\_

5. Private Claims: \_\_\_\_\_

I, Craig W. McVean, in a field survey on July 30, 2003 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

6 - None

7 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

6 - NE 1/16 Cor. Section 33 – Set 2" Alum. Cap on 5/8" x 34" Rebar per Standard BLM procedure. Also fd. 1/2" capped iron #12016 – N65°56'E 4.14' – which we rejected as Cor. '6'.

7 - N 1/16 corner common to section 33 & 34 - Set 2" Alum. Cap on 5/8" x 34" rebar per standard BLM procedure. CL. of N-S Gravel Rd. is 16' W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

6 - NE 1/16 corner section 33  
 2" aluminum cap stamped on a 5/8" X 34" rebar.  
 S10°E 25.03' to set nail & tag in W side of 12" R. Pine  
 S52°W 19.72' to set nail & tag in NW side of 6" R. Pine  
 N70°W 25.47' to set nail & tag in NE side of 10" R. Pine  
 N60°E 2.25' to set nail & tag in SE side of 5" R. Pine  
 Set blue carsonite post with location tag 1' NW  
 N65°56' E 4.14' to Fd. 1/2" CIR #12016

7 - N 1/16 corner common to section 33 & 34  
 2" aluminum cap stamped on a 5/8" X 34" rebar  
 N22°E 19.07" to set nail & tag in W side of 14" Cedar  
 N75°E 33.91' to set nail & tag in S side of 8" Cedar  
 S28°E 24.70' to set nail & tag in W side of 8" Cedar  
 Set blue carsonite post with location tag 1' North  
 N87°39'W 32.26' to Fd. 1/2" CIR #12016 – 0.85' North of line

Signed by: Craig W. McVean  
 Surveyor's Michigan License No.: 39088

Date: 11/10/2003