1994 Alcona County Remonumentation Corner	Alcona County Remonumentation
LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74 Mich. P.A. 1970	Liber Page 103
Filing Requirement of Act 74, Mich. P.A. 1970	RECORDED
Alcona Located In: Corner Code#	
1. Public Land Survey T 25N R 9E	DEC 28 11) 05 AN 194
2. Property Controlling S T R STORY in Section S T R STORY 3. Missellensons	REGISTER CE CLLOS ALCONA COUNTY EL HIGAN pister of Deeds Stamp & File Number
4. Lot No, Recorded Plat	A B C D E F G H I J K L M
5. Private Claims	3
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:	4 7 8 9 10 11 12 6 18 17 16 15 14 13 7 8 19 20 21 22 23 24 9 10 30 30 30 37 36 36
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.	11
A. Description of original monument and accessories and/or subsequent restoration:	13
1843: G.L.O. Survey by Mullett & Burt - Set Post and F Tam 10 - S72W - 19 / Tam 6 - N46W - 20	
 1950: Survey by Clarence F. Aikman - Plat of Huron-Ced B. Description of corner evidence found and/or method applied in restoring or reestablishing 1994: Set 1/2" Iron Rod on the Section Line common to by retracement of the Plat of Huron-Cedar Lakes 	corner: O Sections 23 and 26,
C. Description of monument for corner and accessories established to perpetuate locating the 1994: Replaced with a 5/8" Iron Rod with a 3" Alumin	
to identify the Corner. Referenced - N85°W - 24" W.Pine - 100.42 Feet S70°W - 8" Cedar - 104.28 Feet N70°W - S.E. Cor. Hse 85.55 Feet N25°W - 24" W.Pine - 147.75 Feet	DAVID B. GUTHRIE LAND SURVEYOR NO. 22435
Signed by Dat B. Cuth Date Dec.	28, 1994

Surveyor's Michigan License No. 22435