MAR 0 4 1998

	1997 ALCONA COU	UNTY REMONUMENTATIO	ON CORNER	Alcona Cour	ity	
SECTION		RECORDATION CERT	IFICATE	4	Page	241
For corners in Alcona	Located In:	Corner Code #	CORN 1990 INTY	RECOR		07
(County)				August 2	5 1:00 P	.M. 97
a District and Occasion	T 28NR 7E	K-4	A SOL	3		
Public Land Survey	T R	Caledonia Twp.				
•	T R		APPROVED P A 3 ALCON Date.	Rep		
	T R		5 - 5 m	County	,	
2. Property Controlling	ST R ST R		APPF Date		a Ba	Shar-
in Section 3. Miscellaneous	s r R		"	REGR	STER OF DEE	
Property in Section	s T R		Registe	er of Deeds Star	ກp & File Nເ	ımber
	Recorded Plat			A B C D E	F G H I	JKL
5. Private Ciairis				2 - 6 5		
				3	 	11
Thomas I Fabis	_, in a field survey on	Tune 12 40 97		4 7 8	-9-10-10-1	-1112
do hereby certify that under re	equirements of P.A. 74, Michigan P.A.	of 1970, the corner points me	entionea	ő 18 17	-1615	-1413
in lines 1 and 2 above were in	conformance with regulations and rul	es therefore as required in the	current	7		
Management or by a decree of	his of the United States Department of a Court of Law and/or that the com	ner points mentioned in lines 3	3, 4 and	8 19 20	-21	—23 ——2
5 above were in conformance	e with the rules of the Michigan Boa ablished, re-established, monumente	and of Professional Surveyors	or by a	9		- - -
as expressed below:	apisned, re-established, motorrende	gg, 10-monumented, 10001010	, 100110	10 30 29	-2B27-	—26——26
NOTE: Not more than 4 co	omers, all in the same town and r	ange, may be recorded		11		
on this certificate.			,	12 31 32	-3334	
1988: R.S. Scott A East Utility	Engineering Survey No Assoc. Survey W.O. 1-15 Pole 30.65, N85W Twin con rod 33.00	04 David Guthrie F	Cound 1/2"	iron rod &	referenc	ed:
1997: Found 1/2"	evidence found and/or method iron rod 1.46' North o witnesses: N80W Dead T c in P.P. 30.53', S43W	of another 1/2" iro	on rod. A. 72E 16" Oal	lso found th k 62.68',		3.00'
The position of the position	on of this corner is ac ition of the original o	ccepted as a carefu	ıl and fai	thful perpe	cuation	
				Ç		
C. Description of monu	ment for corner and accessories	established to perpetuate	e locating the	position of the c	orner:	
1997: Set 3" dia	. brass cap, stamped to rod and set a Monument	o identify the cor	ner over t		OF MICH.	40.
Witnesses and the second of th	are: ak - N72E - 62.68' le - S84E - 30.53' ak - S34W - 35.25' Rod P.S. 18660 - N84W	- 33.00'		TE RE	HOMAS L. FABIS LAND EURVEYOR NO. 31591 CAND SU	****
-7/	tomas L. Fabis	Dat	a August	: 15, 1997	** decidental series	
Signed by	-0//00			IGAN STATE BOARD OF PRO	ESSIONAL BURVEYO	RS, JAN. 90, 1971
Surveyor's Michigan Lice	SUSB MO' 31731				REVIS	SED MAY 14, 1975 WISED JAN., 1983