

SURVEY REMONUMENTATION

APR 29 1999

ALLEGAN COUNTY REMONUMENTATION

SECTION

LAND CORNER RECORDATION CERTIFICATE

For corners in

Filing Requirement of Act 74, Mich. P.A. 1970

FILED

.....ALLEGAN..... Located in: .LEE..... Township
Corner Code #

1/28/1999 2:44:39 PM

JOYCE A. WATTS
REGISTER OF DEEDS
ALLEGAN COUNTY, MICH

Register of Deeds Stamp & File Number

1. Public Land Survey T...1..N R..15 W.....G-13.....
T..... R..... SW COR, SEC 34
2. Property Controlling S..... T..... R.....
in Section S..... T..... R.....
3. Miscellaneous S..... T..... R.....
Property in Sec. S..... T..... R.....
4. Lot No., Recorded Plat
5. Private Claims.....

I, George J. Mitchell, in a filed survey on 10/26 thru 11/07/98, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

A. Description of original monument and accessories and/or subsequent restoration:

W. BROOKFIELD 1827 W. ON SOUTH SIDE OF SECTION 34 SET POST AT 80 CHAINS
BEECH 10 N82E 8 LKS BEECH N41-3/4W 24 LKS

COUNTY SURVEYORS RECORDS (NO DATE) STAKE AND WELL POINT TRI 14' MAPLE NWW 108'
10' WILD CHERRY NE 112.4'

COUNTY SURVEYOR'S RECORDS 1968 FD 2" PIPE, RAISED WITH 1" IRON C/L ROAD NORTH 18'
6 FEET WEST OF POWER LINE ST. SIGN NW 54.1' P. POLE NNW 154.5'
T.C.B. NE 96.8' 12' W. CHERRY NE 112.4'

G. MITCHELL P.S. 1977, 1990 L.C.R.C. L.3, P.181 FOUND 1" IRON ST. SIGN NNW 54.15'
TRI W. CHERRY NE 94.8' 8' W. CHERRY SW 30.70' C/L E-W ROAD NORTH 20'

G. MITCHELL P.S. 1993 FOUND 1" IRON 10' W. CHERRY N35E 94.8'
P. POLE N15W 155.20' W. POST DIRECTION SIGN N45E 4.22'

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED NOV 10, 1998
COUNTY REP. [Signature]

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-13) FOUND 5/8" REBAR AND 2" PIPE 30" BELOW FROM CORNER HISTORY AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

THIS CORNER WAS APPROVED BY THE ALLEGAN COUNTY SURVEYORS PEER GROUP ON NOVEMEBR 10, 1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-13) SOUTHWEST CORNER OF SECTION 34, TOWN 1 NORTH, RANGE 15 WEST

REMOVED 5/8" REBAR AND SET 3/4" X 24" IRON PIN WITH ALLEGAN CO. REMON CAP OVER 2" PIPE.

A.C. REMON TAG & NAIL IN WEST SIDE OF 10" TWIN CHERRY	AZ.	040°	84.42 FEET
A.C. REMON TAG & NAIL IN EAST SIDE OF 14" TWIN CHERRY	AZ.	185°	132.21 FEET
A.C. REMON TAG & NAIL IN SE SIDE OF 8" WILD CHERRY	AZ.	255°	127.30 FEET
A.C. REMON TAG & NAIL IN NE SIDE OF POWER POLE	AZ.	250°	154.95 FEET

CORNER IS IN THE CENTER OF "T" INTERSECTION (E-W ROAD HAS BEEN RELOCATED)
CORNER G-13 TO H-13 MEASURED 2602.20 FEET

Signed by George J. Mitchell Date Nov 11, 1998
Surveyor's Michigan License No. 19618



LIBERO 006 PAGE 65