

SURVEY & REMONUMENTATION

APR 25 1995

ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

ALLEGAN
(County)

Located In:

Corner Code #

1. Public Land Survey

T 2N R 14W

L-13 Valley

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

1994 DEC 16 AM 9:55
REGISTER OF DEEDS
ALLEGAN COUNTY, MICHIGAN
Roger A. Elliott

FILED

Register of Deeds Stamp & File Number

I, Donald R. Pitts Jr., in a field survey on September 10, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.-Set $\frac{1}{4}$ Section Post

8" W. Oak N.88°E. 14 Links

10" W. Oak N.75°W. 14 Links

1887-Allegan Co. Surveyor, E.P. Waterman

Stake No Witnesses

1990-Allegan Co. Surveyor, Kirk L. Van Order

24" Maple S.E. 66.64'

Power Pole N.E. 62.36'

Power Pole S.W. 119.5'

24" White Oak N.W. 129.12'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Iron in Mon. Box

24" Maple S.E. 66.64'

Power Pole N.E. 62.36'

24" White Oak N.W. 129.12'

Pulled Iron and set Standard Allegan Co. 3/4" X 24" Remon Iron W/Red Cap #23520 in Mon. Box

Approved by the Allegan Co. Remon. Peer Group on April 12, 1994 and is accepted as a careful and faithful perpetuation of the position of the original corner, and common to L-1, T.1N., R.14W. due to common usage.

Traversed 2630' East & 2661' West

APPROVED REMONUMENTATION CORNER

P.A. 343 OF 1990

ALLEGAN COUNTY

DATE APPROVED 4-12-94

COUNTY REP. Kirk L. Van Order

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


Standard Allegan Co. 3/4" X 24" Remon Iron W/Red Cap 23520 in Mon. Box.

Nail & Allegan Co. Remon Tag in E. Side Power Pole S.40°W. 119.50'

" " " " " in N.E. Side 24" Oak N.40°W. 128.54'

" " " " " in S. Side Power Pole N.70°E. 62.72'

" " " " " in N. Side 26" Maple S.45°E. 66.64'



Signed by Donald R. Pitts Jr.

Date 12 SEPTEMBER 1994

Surveyor's Michigan License No. 25867

LIB 0005 PAGE 044

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983