

Allegan County Remonumentation

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Allegan

Located in:

Corner Code #

{County}

M-6 (E ¼ 13)

1. Public Land Survey

3N 11W

Wayland Twp.

2. Property Controlling in Section

S **T** **R**

3. Miscellaneous Property in Sec

S T R

4. Lot No. _____, Recorded Plat

5. Private Claims

* RE-RECORDING TO CORRECT RANGE LOCATION ON L.6, P. 273.

I, Steven Koerber, in a field survey on Oct. 14, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-6 GLO - John Mullett DS, 1826
B. Oak 7 S10W 42
W. Oak. 14 N37W 41

1. A Gardner May 1, 1879
Stone with "X"
no wits

2. Old notes from Wightman 5-9-1978
set 3/4" Pipe to replace 1/2" ref. Rod on
stone with 'X'
P.K. nail w/ washer in root of hickory
WSW 85.25'
P.K. nail w/ washer in p.pole NNE 85.30'
P.K. nail w/ washer in Hickory NW 40.26'
St. sign SW 43.97' (revised S35°W 45.25')
40.12 CH West to Center of Section

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: C/L road East 5' on C/L road W.

M-6 Found 3/4" iron pipe in Mon. Box
C/L road 5' East
Face of corner fence post S45°W 51.1'
Nail in 14" Hickory S15°E 96.6'

M= 114.95' South to A-6 (W ¼ corner Sec 18-3-10 Barry County)

This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

Peer Group approval November 11, 1997.

Dist to M-5 2645.74'

Dist to M- 7 2658.56'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-6 Set Standard Allegan Co. Mon. (3/4" x 24" Iron Rod with Remon.cap)
Set nail & Allegan Co. Remon. tag in E. side P. Pole N20°W 84.51'
Set nail & Allegan Co. Remon. tag in E. side RR tie fence post S40°W 56.67'
Set nail & Allegan Co. Remon. tag in SE side 14" Hickory S25°E 96.56'
South leg traffic sign S75°E 26.8'
C/L 131st Avenue to West 1' South
C/L Patterson Road 4.5' East
A-6 (W ¼ corner Sec 18-3-10 Barry County) 114.95' South

APPROVED REMONUMENTATION CORNER
P.A. 345 OF 1990
ALLEGAN COUNTY

DATE APPROVED 11-11-97
COUNTY REP. Mark L. Long

original corner.

Signed by

Date 8-10-1999

Surveyor's Michigan License No. 39085