

ALLEGAN COUNTY REMONUMENTATION  
 LAND CORNER RECORDATION CERTIFICATE  
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Allegan (County) Located in: Corner Code #

1. Public Land Survey T4N R14W L-2  
 T R Center  
 T R Sec. 1  
 T R Overisel Twp.

2. Property Controlling S T R  
 in Section S T R  
 3. Miscellaneous S T R  
 Property in Sec. S T R

1995 DEC 14 PM 2:36  
 REGISTER OF DEEDS  
 REGISTER OF DEEDS STAMP & FILE NUMBER

**SURVEY & REMONUMENTATION**

APR 29 1996

**COMMISSION**

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3	7	8	9	10	11	12							
4	18	17	16	15	14	13							
5	19	20	21	22	23	24							
6	30	29	28	27	26	25							
7	31	32	33	34	35	36							

I, Gerald T. Ford, in a field survey on July 1, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
 L-2  
 Corner position not monumented in original government survey. Allegan Co. survey notes August 26-29, 1875 Stake and stone


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-2  
 Established intersection of 1/4 lines and excavated gravel road and found no evidence of stone, also excavated road 11' E on N-S occupation and found no evidence of stone.  
 Set A.C. Remon. iron and cap at intersection of 1/4 lines.  
 Traversed (on road) - 5263.21'  
 Traversed (off road) - 5330.26'  
 Approved by the Allegan Co. Remonumentation Peer Group on November 14, 1995. This position not established by original government surveyors. This monument is accepted as the best available evidence of the position of the corner.

APPROVED REMONUMENTATION CORNER  
 P.A. 345 OF 1990  
 ALLEGAN COUNTY  
 DATE APPROVED 11-14-95  
 COUNTY REP. *[Signature]*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- L-2  
 A.C. Remonumentation iron and cap  
 "X" cut S and 30" CMP culvert AZ 213° 22.85'  
 "X" cut N and 30" CMP culvert AZ 310° 29.81'  
 A.C. Remon. tag and nail W face power pole AZ 205° 35.71'  
 A.C. Remon. tag and nail North face power pole AZ 281° 124.99'  
 SW corner house foundation AZ 290° 257.38'  
 N-S occupation to South East 10'±  
 L-1 (N 1/4 cor. Sec. 1) AZ 356° 47' 47" 2692.07'  
 L-3 (S 1/4 cor. Sec. 1) AZ 176° 47' 47" 2638.19'  
 M-2 (E 1/4 cor. Sec. 1) AZ 87° 20' 48" 2629.51'  
 K-2 (W 1/4 cor. Sec. 1) AZ 267° 20' 48" 2633.70'



Signed by Gerald T. Ford Date November 13, 1995

Surveyor's Michigan License No. 33976

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
 REVISED MAY 14, 1976  
 REVISED JAN., 1983  
 ADAPTED FOR WORD PROCESSING MARCH, 1983