

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Alpena

(County)

Located In

Corner Code #

1. Public Land Survey

T 29N R 8E G-1
T 29N R 8E H-1

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Section

S T R
S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on June 30, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

G-1 – Sec. Cor. comm. to sec.'s 3&4, T29N,R8E

H-1 – North ¼ Corner Section 3, T29N,R8E

1839 – GLO – Lewis Claison – Intersected S. Boundary T30N 1.15 links W. of post.
Cedar 14" S42°W 07 Links
B. Ash 14" S24½°E 37 Links

Corner not set during the Original GLO Survey

2006 – Gary W. St.Charles P.S.#27461 unrecorded Certificate of Survey no corner found set ½" Rebar/Cap

1903 – County survey records Jos. W. McNeil survey for Highway Commissioner J.L. Mathews tied to corner he had previously run.
No witnesses given

N87°W 6.58' 12" Birch
N04°W 7.87' 4" Balsam
N80°E 4.62' 12" Birch
S28°E 10.25' 12" Ash

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

G-1 – Sec. Cor. comm. to sec.'s 3&4, T29N,R8E

H-1 – North ¼ Corner Section 3, T29N,R8E

Dug in wet swamp for remains of cedar stake unable to Find. Reestablished the corner at the intersection of an old North – South road bed and road bed to the East, moved the position South 0.43' to the Township line.

Found ½" bar w/ P.S. Cap #27461 fitting Gary W. St.Charles Survey and witnesses reasonably well.
Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-1 – Sec. Cor. comm. to sec.'s 3&4, T29N,R8E

H-1 – North ¼ Corner Section 3, T29N,R8E

Set a 1"x72" galvanized pipe with Standard DNR Cap

Set a 1"x48" galvanized pipe with Standard DNR Cap

Witnesses:

N45°E 40.35' to set N&T on NW side 3" Cedar
S64°E 25.53' to set N&T on N side 6" Ash
S23°W 39.58' to set N&T on NW side 8" Elm
N53°W 47.24' to set N&T on NE side 3"& 5" Y. Birch

Witnesses:

N88°E 16.91' to set N&T on S side 4" Balsam
* S44°E 10.32' to set N&T on W side 13" Ash
S87°W 15.08' to set N&T on N side 16" R. Maple
*N74°W 6.67' to set N&T on S side 11" W. Birch
*N05°E 7.99' to set N&T on W side 6" Balsam
S87°E 54.45' to DNR Monument South ¼ Corner section 34 T30N,R08E
Set Blue Carsonite Post w/loc. tag 1' North

* Previous witness of record.

Signed by:

Carl T. Kiiskila

Date:

2/9/11

Surveyor's Michigan License No.:

33981

