

SURVEY &
REMONUMENTATION
1994 Alpena County Remonumentation Corner

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED
ALPENA COUNTY MI.
LIBER 1 PAGE 304
Oct 11 10 38 AM '94
REGISTER OF DEEDS

DEC 07 1994

For corners in

Alpena COMMISSION
(County)

Located In:

Corner Code #

1. Public Land Survey	T 31N R 7E	L-9
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Daniel T. Kibbe, in a field survey on June 23, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1855: G.L.O. Re-survey by Butler Ives - set post & referenced: Hemlock 12 - S 23 W - 12 / W. Birch 8 - N 50 E - 15.
1890: County Survey by Wm. H. LeRoy - found ONBT, set 3" sq. cedar stake for corner & referenced.
1961: Monument Witness Record by N.C. Caldwell - set 1" bar from information by LeRoy.
1963: MSHD Construction Plans - referenced 1" bar.
1968: MSHD - Re-witnessed 1/2" iron rod.
1971: Survey by James Scott
1977, 78, 81, 87: Survey by Duane MacNeill - found mon. box.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1994: Found 1/2" iron bar in monument box.

This corner position is compatible with county and local surveys and agrees with MDOT records. This corner position is accepted as a careful and faithful perpetuation of the position of the original corner.

P.A. 345 ALPENA COUNTY
PEER APPROVED Sept. 8, 1994
Paul B. Carter

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1994: Placed 3" aluminum cap stamped to identify the corner over existing 1/2" iron rod in monument box.

Referenced:

N 17° W - set nail in 22" Norway Pine (set over old nail & tag that has been grown over. Tree has old blaze) - 102.94'
S 25° E - set nail in 20" Norway Pine (set over old MSHD nail & tag that has been grown over. Tree has old blaze) - 89.22'
S 10° W - set nail in 9" Maple - 83.39'
S 51° W - set nail in T. pole - 90.40'
N 08° E - center 10" stump - 85.5'

Signed by

Daniel T. Kibbe

Date August 3, 1994

Surveyor's Michigan License No. 37278

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS JAN. 14, 1977
RENEWED JAN. 14, 1994

