

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 6 T 47N R 33W	7
	S 6 T 47N R 33W	14
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 14 01/31/2012 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(7-Sec. 6) North 1/16 corner between Sections 5 and 6. Not previously monumented.

(14-Sec. 6) South 1/16 corner between Sections 5 and 6. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7-Sec. 6) Established the position for the corner on the Section line between Sections 5 and 6 1314.06' (20.00 ch. R) north of the Quarter corner and 1262.16' (19.21 ch. R) south of the Section corner on the Township line, the position being proportionate to the dimensions given on the original plat of this township.

(14-Sec. 6) Established the position for the corner midway and on the Section line between Section corner 1314.06' south and Quarter corner 1314.06' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7) Set 1"IDx32" I.pipe with 4" alum. MNDR cap.  
Set measuring nail with MDNR tag in the side of:  
15" Cedar S88E 34.3' mrkd "1/16S BT"  
3" Sugar S53E 3.2' do  
5" Sugar S45W 3.85' do  
2" twin Sugar N30E 25.4' " X X "  
Set sq'd cedar post adjacent.  
Bearings are magnetic.

(14) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
4" Sugar N49E 17.7' mrkd "1/16S BT"  
9" Sugar S32E 5.4' do  
5" Sugar S46W 24.9' do  
4" Sugar N70W 21.8' do  
Set sq'd cedar post adjacent.  
Bearings are magnetic.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 04/26/2012

For the Michigan Department of Natural Resources, Forest Resources Division

