

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 10 T 48N R 32W	3
	S T R	(GCDB 400560)
	S 10 T 48N R 32W	11
3. Miscellaneous Property in Sec.	S T R	(GCDB 420520)
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 05/28/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3-Sec. 10) North 1/16 corner between Sections 9 and 10. Not previously monumented.

(11-Sec. 10) Southwest 1/16 corner of Section 10. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 10) Established the position for the corner midway and on the Section line between Section  
corner 1297.36' north and Quarter corner 1297.36' south.

(11-Sec. 10) Established the position for the corner at the intersection of straight lines  
connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
4" Balsam N16°W 11.25' mrkd "1/16S BT"  
7" Spruce East 20.6' do  
6" Spruce S34°W 6.85' do  
6" Spruce N89°W 6.6' do  
Set sq'd cedar post adjacent.  
E= 7900058.368 N= 199949.747

(11) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" B.Spruce N17°W 18.4' mrkd "1/16S BT"  
6" B.Spruce N46°E 16.35' do  
8" B.Spruce S11°E 6.45' do  
7" Tamarack S59°W 14.0' do  
Set sq'd cedar post adjacent.  
E= 7900443.883 N= 199147.250

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)  
Coord. Ref.=NGS PID RL1468: N= 199449.721 m. E= 7900600.011 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 06/18/2014

For the Michigan Department of Natural Resources, Forest Resources Division

