

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 10 T 48N R 32W	5
	S T R	(GCDB 440560)
	S 10 T 48N R 32W	4
3. Miscellaneous Property in Sec.	S T R	(GCDB 420560)
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 05/28/14 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(5-Sec. 10) Center-North 1/16 corner, Section 10. Not previously monumented.

(4-Sec. 10) Northwest 1/16 corner, Section 10. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(5-Sec. 10) Established the corner midway and on a straight line between Quarter corner 1304.98'
north and the Center of Section 10 1304.98' south.

(4-Sec. 10) Established the corner at the intersection of straight lines connecting opposite 1/16
corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(5) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Poplar N11°E 9.15' mrkd "1/16S BT"
6" Poplar N81°E 9.45' do
5" Poplar S24°E 8.1' do
3" Spruce West 0.8' do
Set sq'd cedar post adjacent.
E= 7900863.561 N= 199930.451

(4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Balsam N21°E 5.4' mrkd "1/16S BT"
6" Poplar N72°E 7.55' do
5" Balsam S43°E 12.1' do
6" Poplar S87°W 7.6' do
Set sq'd cedar post adjacent.
E= 7900460.960 N= 199940.096

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=NGS PID RL1468: N= 199449.721 m. E= 7900600.011 m.

Signed by Stephan J. Szyszkoski Date 06/18/2014
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

