

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga Located In: Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Sec.
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numerical data for registration stamp.

I, Stephan J. Szyszkoski, in a field survey on 11/12/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(3-Sec. 6) North 1/16 corner between Section 6 T48N-R32W and Section 1 T48N-R33W. Not previously monumented.

(15-Sec. 6) West 1/16 corner between Sections 6 and 7. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(3-Sec. 6) Established the position for the corner on the Range line between Quarter corner 1328.22' south (US Plat = 20.00 ch.) and Township Corner 1208.68' north (US Plat = 18.20 ch.), proportionate to the US record.

(15-Sec. 6) Established the position for the corner on the Section line between Quarter corner 1320.16' east (US Plat = 20.00 ch.) and Section corner 1021.80' west (US Plat = 15.48 ch.), proportionate to the US record. The position falls in a high-voltage power line clearing.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 4" Sugar N37°E 15.1' mrkd "1/16S BT" 9" Sugar S35°E 7.9' do 7" Sugar S87°W 15.95' do 12" Sugar N11°W 13.95' do Set sq'd cedar post adjacent. E= 7895355.055 N= 201652.146

(15) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 9" Sugar N12°E 28.2' mrkd "1/16S BT" 10" Sugar N60°E 46.4' do 5" Sugar N24°W 34.4' do N'ly of two OH power poles S17°E 28.3' Set sq'd cedar post adjacent. E= 7895642.249 N= 200432.276

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL1468: N= 199449.725 m. E= 7900599.998 m.

Signed by [Signature] Date 03/18/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division