

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T 49N R 32W	J3
	T 49N R 32W	M3
	T	
2. Property Controlling in Section	S T	
	S T	
	S T	
3. Miscellaneous Property in Sec.	S T	
	S T	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on J3 12/06/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(J3) Quarter corner common to Sections 2-11. 1852 - Established by Guy Carleton Deputy Surveyor
midway and on the Section line between Section corners 40.31 chains east and west. 1975 - Mead Corp.
notes state that the mile was chained in 1942 by Norman T. Thompson RLS and that he set the corner
and two NBTs: Maple 10" N29W 15.6', Cherry 6" N65W 6.2'. Foresters Ervast and Lazzari found the 1942
Maple N29W NBT at record bearing and distance from an iron pipe, cedar post adjacent, and a Ford
Motor Co. location poster on a Balsam 5" N66W 16.3' distant. They made two new NBTs: Sugar 4.0" S46E
11.0', B.Cherry 5.6" N77E 8.8'.

(M3) Corner common to Sections 1-12 T49N-R32W and Sections 6-7 T49N-R31W. 1846 - Established by
Wm.A.Burt Deputy Surveyor. Set Spruce post. Spruce 4 N19E 24 links, Tamk 4" S59W 7 links.
Additional witnesses by Guy Carleton Deputy Surveyor, 1852: Spruce 8" N50W 18 links, Fir 10" S85E 25
links. Undated notes (probably 1941) by Norman T. Thompson RLS state that he found the Tamarack BT
down and set post at the corner position.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(J3) Found a 1"ID iron pipe at record bearing and distance from the 1975 NBT Sugar S46E and the
Balsam with old location tag N66W. From a position which is midway and on the Section line between
Section corners I3 and K3, this pipe is 4.5' west and 17.4' north and I accept same as the best
available evidence of the position of the original corner.

(M3) Found a 1"ID Iron pipe adjacent to a rotted post point preserved below the ground water line.
Top portion of post was recovered laying down below the moss and was found to be scribed "T49N R".
At record bearing and distance, found the very rotted remains of what could be the Tamarack BT S59W 7
links, no marks visible. A B.Spruce S67W 38.3' and a Y.Birch N08W 11.3' with overgrown blazes face
the pipe, which has a pinched top. A Ford Motor Co. location poster dating to 1964 faces the pipe on
a nearby tree. I accept the pipe as the best available evidence of the position of the original
corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(J3) Found 1"ID iron pipe.
6" Sugar S40E 11.1' mrkd "1/4S NBT"
10" Sugar S57W 2.5' do
5" Sugar N14W 13.3' do
5" Sugar N73E 27.85' do
Set sq'd Cedar post adjacent.
Bearings are magnetic.

(M3) Fd 1"ID I.pipe with pinched top.
Set measuring nail with MDNR tag in the side of:
9" B.Spruce S67W 38.3' overgrown blazes
4" B.Spruce N33W 9.25' mrkd "S1 NBT"
4" Y.Birch N75E 10.2' "S6 NBT"
4" Maple in clump S22E 22.45' "S7 NBT"
Set sq'd Cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 07/27/2011

For the Michigan Department of Natural Resources, Forest Management Division

