

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 31 T 49N R 32W	11 (GCDB 120120)
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 11/09/15 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 31) Southwest 1/16 corner, Section 31.
Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 31) Established the position for the corner at the intersection of straight lines
connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx28" I.pipe with 2" alum. MDNR
cap. Set measuring nail with MDNR tag in the
side of:
7" Sugar N30°E 9.95' mrkd "1/16S BT"
9" Sugar S68°E 5.35' do
4" Sugar S13°W 16.2' do
4" Sugar S84°W 10.0' do
Set sq'd cedar post adjacent.
E= 7895683.574 N= 202412.281



Bearings are magnetic. Coordinates are MCS83 in meters, NAD83 (2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID RL1468: N= 199449.725 m. E= 7900599.998 m.

Signed by Stephan J. Szyszkoski Date 03/18/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division