

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: September 11, 2017

For corner(s) in: Baraga County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

a. S 19 T 49N R 32W 8 (GCDB 120340)
b. S 30 T 49N R 32W 15 (GCDB 120200)
b. S 31 T 49N R 32W 1 (GCDB 120200)
S T R

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8	●	19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11	●													11
12		31		32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) Center-West 1/16 corner, Section 19. Not previously monumented.

b.) West 1/16 corner between Sections 30 and 31. Not previously monumented.



Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner on a straight line between Quarter corner 1055.10' west (15.22 ch. derived from GLO plat) and the Center of Section 19 1386.43' east (20.00 ch. GLO plat), being 20 chains, proportionate, west of the Center.

b.) Established the position for the corner on the Section line between Section corner 1100.69' west (GLO plat 15.40 ch.) and Quarter corner 1429.46' east (GLO plat 20.00 ch.), being 20 chains, proportionate, west of the Quarter corner. The position for the corner falls on a cliff and was not monumented directly. Set a WITNESS CORNER monument 158.74' east of the corner position, and on the Section line.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Spruce N55°E 2.5' mrkd "1/16S BT"
11" Sugar S53°E 7.65' do
6" Sugar S33°W 18.0' do
3" Sugar N74°W 15.6' do
Set sq'd cedar post adjacent.
E= 7895760.544 N= 206000.706

b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap
158.74' east of the corner, on the Section line,
for a WITNESS CORNER.
Set measuring nail with MDNR tag in the side of:
7" Cedar S65°E 3.3' mrkd "WC BT"
9" Cedar S07°E 3.0' do
4" Sugar S57°W 7.65' do
7" Sugar N38°W 13.9' do
Set sq'd cedar post adjacent.
E= 7895761.748 N= 203610.435 (the W.C.)

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.

Coord. Ref.=NGS PID RL0041: N=210246.994 m. E=7895426.985 m.

Stephan J. Szyszkoski

10/04/2017

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908