

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 35 T 49N R 33W	1 (GCDB 520200)
	S 35 T 49N R 33W	4 (GCDB 520160)
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 09/01/15 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(1-Sec. 35) West 1/16 corner between Sections 26 and 35.
Not previously monumented.

(4-Sec. 35) Northwest 1/16 corner, Section 35.
Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(1-Sec. 35) Established the position for the corner midway and on the Section line between Section
corner 1308.45' west and Quarter corner 1308.45' east.

(4-Sec. 35) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16 corners, those to the north and west being monumented.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(1) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Maple N02°W 23.85' mrkd "1/16S BT"
18" Maple S68°E 15.0' do
8" Maple S20°W 23.15' do
9" Maple N62°W 15.25' do
Set sq'd cedar post adjacent.
E= 7892570.964 N= 203667.012

(4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Sugar S34°E 0.85' mrkd "1/16S BT"
4" Sugar S34°W 8.65' do
12" Sugar S83°W 8.75' do
7" Sugar N25°W 12.85' do
Set sq'd cedar post adjacent.
E= 7892564.406 N= 203264.808

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID RL0476: N= 196482.411 m. E= 7879234.516 m.

Signed by Stephan J. Szyszkoski Date 10/27/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

