

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga

(County)

Located In:

Corner Code #

1. Public Land Survey

T 50N R 34W

F7

T R

T R

T R

S

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Jul 17 2006

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(F7) Quarter corner reestablished in 1974 by A.O. Enger RLS, on line between Sec. Corners 40.116 ch. to E and to N. Set 1" IDx36" iron pipe with 3 1/2" alum. cap. NBTs: Red Oak 11 S04E 15.9', Red Oak 13 N43E 9.0'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(F7) Recovered the 1974 monument in good condition and at record bearing and distance from the 1974 NBTs, both in good condition. Determined that the monument was placed in an erroneous position, approx. N69W 19.7' from the single proportionate position intended in 1974. Destroyed the 1974 monument and reestablished the corner at the intended position, midway and on the section line between corners E7 and G7 2642.91' East and West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(F7) Set 1" IDx32" I. pipe with 4" alum. MDNR cap. Set measuring nails in:
13" Oak S64W 20.1' mrd "1/4S NBT" *
14" Oak N38W 18.3' do *
6" Oak N05E 20.3' do
6" Oak N50E 10.5' do
Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag. * denotes 1974 NBT with new markings made.



Signed by

Stephan J. Szyszkoski

Date

10/24/06

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Office of Land and Facilities