

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T 51N R 30W T 51N R 30W T R	E5 D5
2. Property Controlling in Section	S T R S T R S T R	
3. Miscellaneous Property in Sec.	S T R S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	5		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 08/15/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(E5) Corner common to Sections 8-9-16-17. 1846 - Established by Hubbard and Ives, Deputy Surveyors. Set post. Hemlock 15" S40°W 43 links, Hemlock 12" N65°E 17 links. May 5, 1942 - Norman T. Thompson RLS notes that he found the original BTs "OK down" and made new witnesses: Hemlock 6" S30°E 7'4", Sugar 6" S09°W 15'7". No mention of any monumentation.

(D5) Quarter corner common to Sections 8 and 17. 1846 - Established by Hubbard and Ives, Deputy Surveyors, midway and on the Section line between Section corners 40.04 chains east and west. Set post. Ironwood 8" S11°W 12 links, Hemlock 5" North 03 links. May 4, 1942 - Norman T. Thompson RLS notes that he found the Hemlock OBT "O.K. down stub". "At 1/4 cor. Set post 1" iron pipe. New B.T. Sugar 12" N80°E 23'9", Hem. 5" S02°E 18'2". "

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(E5) The original post and accessories were not recovered. The 1942 new bearing trees were not recovered. Found a 3/4" ID iron pipe with blazed trees facing it. Accepted the pipe as the N.T. Thompson 1942 monument or a perpetuation of the position thereof and as a careful and faithful perpetuation of the position of the original corner. Distances 5284.30' north (5280' R) and 2626.06' west (2640' R) to found corner monuments check well with the original record.

(D5) Found a 1"ID iron pipe, set firmly, at record bearing and distance from the 1942 Hemlock NBT S02°E (S02°W meas.) 18'2", with double overgrown blazes. Accepted same as a careful and faithful perpetuation of the position of the original corner. Distances east and west to Section corners are found to be 2626.06' and 2611.58', respectively.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(E5) Set 1"IDx28" iron pipe with 2" alum. MDNR cap in the place of a found 3/4" ID iron pipe. Set measuring nail with MDNR tag in the side of:  
11" W.Ash N63°E 4.3' mrkd "S9 NBT"  
7" Sugar S69°E 26.25' "S16 NBT"  
5" Ironwood S01°W 14.6' "S17 NBT"  
10" Y.Birch N54°W 24.4' "S8 NBT"  
Set sq'd cedar post adjacent.  
E= 7913839.574 N= 227311.381

(D5) Found 1"ID iron pipe. Drove 2" dia. Alum. MDNR cap onto the pipe. Set measuring nail with MDNR tag in the side of:  
14" Hemlock S02°W 18.6' old blazes (1942 NBT)  
6" Sugar N31°E 13.65' mrkd "1/4S NBT"  
5" Sugar S60°W 12.6' do  
13" Hemlock N41°W 22.4' do  
Set sq'd cedar post adjacent.  
E= 7913039.321 N= 227323.942

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)  
Coord. Ref.=NGS PID D08499: N= 221257.624 m. E= 7884435.169 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 10/08/2013

For the Michigan Department of Natural Resources, Forest Resources Division

