

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

|                                       |                  |               |
|---------------------------------------|------------------|---------------|
| Baraga<br>(County)                    | Located In:      | Corner Code # |
| 1. Public Land Survey                 | T R              |               |
|                                       | T R              |               |
|                                       | T R              |               |
| 2. Property Controlling<br>in Section | S 26 T 52N R 30W | 11            |
|                                       | S 26 T 52N R 30W | PCC S. of I10 |
|                                       | S T R            |               |
| 3. Miscellaneous<br>Property in Sec.  | S T R            |               |
|                                       | S T R            |               |
| 4. Lot No. , Recorded Plat            |                  |               |
| 5. Private Claims                     |                  |               |

Register of Deeds Stamp & File Number

|    | A  | B | C  | D | E  | F | G  | H | I  | J | K  | L | M  |
|----|----|---|----|---|----|---|----|---|----|---|----|---|----|
| 1  |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 2  | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   |    |
| 3  |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 4  | 7  |   | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |
| 5  |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 6  | 10 |   | 9  |   | 8  |   | 7  |   | 6  |   | 5  |   | 4  |
| 7  |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 8  | 13 |   | 12 |   | 11 |   | 10 |   | 9  |   | 8  |   | 7  |
| 9  |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 10 | 16 |   | 15 |   | 14 |   | 13 |   | 12 |   | 11 |   | 10 |
| 11 |    |   |    |   |    |   |    |   |    |   |    |   |    |
| 12 | 19 |   | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |
| 13 |    |   |    |   |    |   |    |   |    |   |    |   |    |

I, Stephan J. Szyszkoski, in a field survey on 11 04/18/2011 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 26) Southwest 1/16 corner, Section 26. Not established in the original survey.

(PCC S. of I10) Property Controlling Corner, being the northwest corner of the South 990 feet of the  
Northwest 1/4 of the Southwest 1/4 of Section 26. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 26) Established the corner at the intersection of straight lines connecting opposite 1/16  
corners.

(PCC S. of I10) Established the corner on the Section line between Quarter corner I10 331.49' north  
and 1/16 corner #10, Sec. 26 990.01' south, being 990 feet, as measured at right angles, from the  
south 1/16 line of Section 26. The position for the corner falls on the edge of a dirt woods road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
15" Hemlock N30E 8.4' mrkd "1/16S BT"  
4" Sugar S87E 15.55' do  
4" Y.Birch S50W 31.0' do  
4" Y.Birch N70W 10.3' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

(PCC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
The monument is buried 5" below ground.  
Set measuring nail with MDNR tag in the side of:  
4" Sugar N33E 17.8' mrkd "X" at B.H.  
6" Sugar N67E 8.25' do  
5" Sugar S24E 24.0' do  
11" Maple N89W 21.45' do  
Set sq'd Cedar post adjacent.  
Bearings are magnetic.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 05/18/2011

For the Michigan Department of Natural Resources, Office of Land and Facilities

