

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____ _____ _____
2. Property Controlling in Section	S 31 T 52N R 30W S 31 T 52N R 30W S _____ T _____ R _____	10 8 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 06/26/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(10-Sec. 31) South 1/16 corner between Section 31 T52N-R30W and Section 36 T52N-R31W. Not previously monumented.

(8-Sec. 31) West 1/16 corner, Section 31. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(10-Sec. 31) Established the position for the corner midway and on the Range Line between Section corner 1321.85' south and Quarter corner 1321.85' north.

(8-Sec. 31) Established the position for the corner on a straight line between Center of Section 31 1319.89' east (20.00 ch. GLO) and Quarter corner 1387.23' west (21.02 ch. GLO), being proportionate to the dimensions derived from the original U.S. plat of this township.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
8" Y.Birch N02°E 30.1' mrkd "1/16S BT"  
9" Maple S03°W 10.9' do  
8" Y.Birch S34°W 19.7' do  
5" Maple N82°W 22.0' do  
Set sq'd cedar post adjacent.  
E= 7910669.101 N= 230960.222

(8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" Sugar N75°E 15.6' mrkd "1/16S BT"  
14" Hemlock S01°W 24.9' do  
16" Hemlock S85°W 25.6' do  
7" Sugar N43°W 8.2' do  
Set sq'd cedar post adjacent.  
E= 7911093.612 N= 231355.627

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID D08499: N= 221257.624 m. E= 7884435.168 m.

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 08/15/2013

For the Michigan Department of Natural Resources, Forest Resources Division

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 1, 1971  
REVISED JAN. 1979  
REVISED JAN. 1993  
REVISED JAN. 1995

