

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Baraga Located In: Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Sec.
4. Lot No. , Recorded Plat
5. Private Claims

I, Stephan J. Szyszkoski, in a field survey on 03/21/16 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(14-Sec. 16) South 1/16 corner between Sections 15 and 16. Not previously monumented.

(13-Sec. 16) Southeast 1/16 corner, Section 16. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(14-Sec. 16) Established the position for the corner midway and on the Section line between Section corner 1317.32' south and Quarter corner 1317.32' north.

(13-Sec. 16) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the east and south being monumented.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(14) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 6" Y.Birch N24°E 6.6' mrkd "1/16S BT" 5" Hemlock N89°E 4.85' do 13" Hemlock S07°E 16.5' do 6" Hemlock N78°W 10.0' do Set sq'd cedar post adjacent. E= 7886646.118 N= 236214.431

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 8" Cedar N39°E 11.8' mrkd "1/16S BT" 9" Y.Birch S27°E 17.05' do 4" Sugar S12°W 19.6' do 10" Sugar N83°W 3.9' do Set sq'd cedar post adjacent. E= 7886239.681 N= 236220.788



Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for recording deed stamps and file numbers.

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL1540: N= 235001.700 m. E= 7887187.199 m.

Signed by [Signature] Date 03/30/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division