

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Benzie
(County)
Located In
Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Section

4. Lot No:
Recorded Plat:
5. Private Claims:

I, Craig W. McVean, in a field survey on May 3, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 in a grid pattern.

A. Description of original monument and accessories and/or subsequent restoration:

NWSW 1/64 - No Date - CSR L. 2, p. 40 - G. Langford - Shows Corner

CWNWSW 1/256 - No Date - CSR L. 2, p. 40 - G. Langford - Shows Corner

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

NWSW 1/64 - Cor. Sec. 36 - being the NE Corner of the SW 1/4 of the NW 1/4 of the SW 1/4 of Sec. 36 - Set 2" Alum. Cap on 5/8" x 34" rebar per Standard BLM procedure. No evidence of Langford position.

CWNWSW 1/256 - being the SE Cor. of the W 1/2 of the NW 1/4 of the NW 1/4 of the SW 1/4 of Sec. 36 - Set 2" Alum. Cap on 5/8" x 34" rebar per Standard BLM procedure. No evidence of Langford position.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NWSW 1/64 - Stamped 2" Alum. Cap on 5/8" x 34" iron rebar. Set Blue Carsonite Post with loc. tag 1' SW. S22°E 66.02' to set N & T in SW side 3" J. Pine S2°W 23.83' to set N & T in W. side 3" J. Pine S53°W 30.08' to set N & T in NW side 7" Cherry N84°W 50.94' to set N & T in N. side 10" Ironwood

CWNWSW 1/256 - Stamped 2" Alum. Cap on 5/8" x 34" iron rebar. Set Blue Carsonite Post with Loc. tag 1' SW. S60°E 17.23' to set N & T in N. side Tw. 6" Cherry S2°E 20.48' to set N & T in W. side 8" J. Pine N59°W 30.47' to set N & T in NE side 3" J. Pine N5°W 40.85' to set N & T in E. side 10" Cherry

Signed by:

Craig W. McVean

Date:

5/8/2012

Surveyor's Michigan License No.:

39088

