

RATIFIED BY THE BERRIEN COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

BERRIEN COUNTY REMONUMENTATION

FOR CORNERS OF: Berrien  
County LOCATED IN: CORNER CODE NUMBER

1. PUBLIC LAND SURVEY T. 6 N. S., R. 17 E. W. M-11

2. PROPERTY CONTROLL-  
ING IN SECTION 25 T. 6 N. S., R. 17 E. W.

3. MISCELLANEOUS  
PROPERTY IN SECTION T. N. S., R. E. W.

4. LOT NO. , RECORDED PLAT 08/30/94 111#2168 A99

5. PRIVATE CLAIMS 08/30/94 111#2168 A99

REGISTER OF DEEDS  
STAMP AND FILING NUMBER

I, Robert W. Prestine, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June, 1994, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

M-11

SE. cor. Sec. 25

Set post Wm. Brookfield D.D. March 1827  
Blue Ash 22" S 28-3/4° W 22 lks.  
Beech 8" N 14 1/2° W 31 lks.

SURVEY &  
REMONUMENTATION

SEP 15 1994

COMMISSION

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-11

Found 1/2" pipe set by self, August 1974 in open field in line with East 1/2 cor. and 1/8 cor. and doubled distance.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-11

Removed 1/2" pipe and set Berrien County conc. monument with remonumentation cap 14" deep with old irons around. (in open field)

36" Sugar N 87° 15' W 305.60' Nail & washer Nly. side  
16" Beech N 64° 05' W 317.05' Nail & washer Nly. side  
Center I. & M. Elec. Co. Tower N 57° 10' E 1129.90'  
Cass County cor. South 14.45'

SIGNED BY Robert W. Prestine DATE August 27, 1994

SURVEYOR'S MICHIGAN REGISTRATION NO. 18662

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

LIBER

3 PAGE 115

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

