

APPROVED

Date 10-21-97
CALHOUN COUNTY
REMONUMENTATION.

For corners in

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

24 OCT 97 12:00 P.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

LIBER 1973 PAGE 177

Register of Deeds Stamp & File Number

CALHOUN

(County)

BEDFORD

Located in:

Corner Code #

1. Public Land Survey

T 1S R 8W

C-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, ROBERT R. CARR, in a field survey on SEPTEMBER 29, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1826 G.L.O. SYVESTER SIBLEY D.S. SET ORIGINAL CORNER
1888 RESURVEY BY SETH PRATT FOUND PIT OF STONES AND POST AT CORNER
U.S. BEARINGS GONE.
1972 L.C.R.C. BY MILTON DEKEYSER #12019 FOUND RAILROAD SPIKE
RAILROAD SPIKE WITNESSED BY: JAMES KING 1987, ROBERT CARR 1992 AND 1995.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

SURVEY &
REMONUMENTATION

APR 07 1998

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: SECTION

FOUND RAILROAD SPIKE WITH THREE 1972 DEKEYSER WITNESSES REMAINING
DUG BELOW, BUT FOUND NO OTHER EVIDENCE OF CORNER.
INTERSECTION HAS BEEN EXCAVATED WITH ROAD CONSTRUCTION.
ACCEPTED RAILROAD SPIKE AS BEST EVIDENCE OF CORNER AND
REPLACED WITH BERNTSEN MONUMENT IN MONUMENT BOX.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BERNTSEN MONUMENT IN MONUMENT BOX
SET SPOTTER IN UTILITY POLE, S34dE 45.45 FEET.
SET SPOTTER IN UTILITY POLE, N30dE 69.51 FEET.
SET SPOTTER IN UTILITY POLE, N35dW 95.90 FEET.
SET SPOTTER IN 30" OAK, N54dW 90.16 FEET.



Signed by

Surveyor's Michigan License No. 20704

Date OCTOBER 20, 1997