

OCT 24 1994

COMMISSION

APPROVED

Date 8-17-94
CALHOUN COUNTY
REMONUMENTATION.

CALHOUN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
CALHOUN COUNTY
RECORDED

18 AUG 94 12:13 P.M.

ANNE B. NORLANDER
CLERK - REGISTER OF DEEDS

For corners in

CALHOUN (County) ATHENS TWP	Located In:	Corner Code #
1. Public Land Survey	T <u>4</u> S R <u>8</u> W	E-13
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

I, ROBERT R. CARR, in a field survey on AUGUST 4, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

ORIGINAL CORNER SET BY DEPUTY SURVEYOR, ROBERT CLARK, 1826.
 RE-SURVEY BY COUNTY SURVEYOR, F.A. COURTWRIGHT, 1896.
 NO EVIDENCE OF STAKE OR BEARING TREES FOUND.
 SET CORNER AT INTERSECTION OF FENCES
 8" POPLAR S22°E 6-1/4 LKS.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND TWO 4" HOLLOW TILES & PIECES OF BRICK AT INTERSECTION OF FENCES NORTH, SOUTH & WEST.
 REMOVED TOP TILE AND SET BERNTSEN: MONUMENT INSIDE BOTTOM TILE.

LIBER 1763 PAGE 769

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

BERNTSEN: MONUMENT WITH BRONZE CAP IN HOLLOW CLAY TILE.
 NAIL & SPOTTER IN SOUTH SIDE 8" CHERRY S60°E 13.85 FT.
 NAIL & SPOTTER IN WEST SIDE 8" CHERRY S02°E 18.80 FT.
 NAIL & SPOTTER IN SOUTH SIDE 4" MULBERRY S70°E 3.42 FT.
 NAIL & SPOTTER IN SOUTHWEST SIDE 14" CHERRY N55°W 16.74 FT.



Signed by Robert R. Carr
 Surveyor's Michigan License No. 20704

Date AUGUST 15, 1994