

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey T R
T R
T R
T R
2. Property Controlling S 7 T 42N R 2E 2
in Section S 19 T 42N R 2E 9
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

9 Sep 01 2005
2 Oct 10 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(2-Sec. 7) East 1/16 corner between Sections 6 and 7. Not established in the original survey. Found no subsequent record.
(9-Sec. 19) East 1/16 corner, Section 19. Not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(2-Sec. 7) Established the corner midway and on the section line between Quarter corner 1351.55' west and Section corner 1351.55' east.
(9-Sec. 19) Established the corner midway and on a straight line between Quarter corner 1316.41' east and Center of Section (unmonumented) 1316.41' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(2) Set 1"IDx36" I.pipe with 4" alum.
MDNR cap. Set measuring nails in:
7" Cedar N34W 16.6' mrkd "E1/16 BT"
6" twin Cedar S80W 1.6' do
8" Cedar S11W 28.85' do
8" Cedar N67E 28.6' do

Bearings are magnetic. Distances are to nail with tag.

(9) Set 1"IDx35" I.pipe with 4" alum.
MDNR cap. Set measuring nails in:
5" Balsam N28E 14.43' mrkd "E1/16 BT"
12" R.Pine S17E 18.78' do
12" Spruce N89W 27.4' do
6" W.Birch S64E 31.2' do

Bearings are magnetic. Distances are to nail with tag.



Signed by

Stephan J. Szyszkoski
33986

Date

1/10/06

Surveyor's Michigan License No. _____
For the Michigan Department of Natural Resources