

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Chippewa	Located In:	Corner Code #
(County)		
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 9 T 42N R 2E	12
	S 9 T 42N R 2E	13
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 12 09/02/2009 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12-Sec. 9) South 1/16 corner, Section 9. Not established in the original survey.

(13-Sec. 9) Southeast 1/16 corner, Section 9. Not established in the original survey. Found no
subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12-Sec. 9) I found an iron pipe with plastic cap #11367 (Joseph Potwardowski, RLS), in good
condition, substantially at the position for the corner, namely, midway and on a straight line
between Quarter corner 1321.31' south and Center of Section 1321.31' north. Accepted the monument as
a careful and faithful determination of the position of the corner.

(13-Sec. 9) Established the corner at the intersection of straight lines connecting opposite 1/16
corners. From the corner thus established, I found a 1/2" uncapped rebar, not of record, set by
persons unknown, N03W (true bearing) 5.1' distant, which I did not accept as marking the position for
the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) Fd. capped iron pipe "RLS 11367"
Set measuring nail with MDNR tag in the side of:
12" Cedar S20E 37.7' mrkd "S1/16 BT"
8" Cedar S26W 45.25' do
7" Balsam S58W 26.75' do
6" Balsam S87E 18.65' do
Bearings are magnetic.

(13) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
18" Oak S15E 48.25' mrkd "SE1/16 BT"
5" Oak N51W 4.5' do
9" Oak N85E 14.4' do
Fd. 1/2" rebar N05E 5.1'
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 10/15/2009

For the Michigan Department of Natural Resources, Office of Land and Facilities

