LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner

For corners in

Chippewa County	Located	i in:		Corne	r Code#
1 ₁ Public Land Survey		T44N T T	R1W R R	J-3	
Property Controlling in Section Miscellaneous Property in Sec.	s s s	T T T T	R R R REN R R	MONU	VEY & MENTATION

47.00 LAND CORNER

\$2.00 MSSR 2 FEB 2001 3:49:03 PM Receirt #1103 RECEIVED FOR RECORD CHIPPEWA COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

PAGE 190 ROOK 11

2 3

Register of Deeds Stamp & File Number

, Recorded Plat Lot No.

5. Private Claims

SECTION

I, Keith R. Waters, in a field survey on March 15, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

5 6 7 9 10 28 11 12

A. Description of original monument and accessories and/or subsequent restoration:

J-3 1/4 Corner Common to Sections 2 & 11, T44N, R1W.

1845 - Original corner established by James H. Mullett. Witnesses: Birch 10, N10°W 25 links - Hemlock 16, S25°W 11 links.

Found no evidence of subsequent restoration of this corner.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being reestablished as part of the Chippewa County Remonumentation Program. Found no evidence of the original corner. Reestablished corner by single proportionate measurement on line between the section corner at K-3 to the east and the section corner I-3 to the west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Placed a ¼" x 24" rebar with a stamped aluminum Chippewa County Remonumentation cap the corner location. Witnesses:

Nail and plastic witness tag #33142 in blazed 24" White Pine, N65°W 20.30"

Nail and plastic witness tag #33142 in blazed 4" Balsam Fir, N52°E 14.15'

Nail and plastic witness tag #33142 in blazed 4" White Birch, S50°E 10.40'

Nail and plastic witness tag #33142 in blazed 20" White Pine, S67°W 56.28"

TE OF MICHIGAN WATERS ROTESSIONAL SURVEYOR Nin 33142 POFESSIONAL

Date (2-29-00

Surveyor's Michigan License No. 33142