LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Cornet .00 LAND CORNER

For corners in

Chippewa County	Located in:	Corner Code #
1. Public Land Survey	T4 T T	4N R1W J-7 R R R
Property Controlling in Section	S T	R SURVEY & REMONUMENTATION
Miscellaneous Property in Sec.	S T S T	R R FEB 2 3 2001

\$2.00 MSSR 2 FEB 2001 3:50:13 PM Receist #1103 RECEIVED FOR RECORD CHIPPENA COUNTY - STATE OF MICHIGAN SHARON H. KENNEDY, REGISTER OF DEEDS

FOOK 11 PAGE 194

2 3 4

5

6

7

8

q

10

11

Register of Deeds Stamp & File Number

anninana (markana)

, Recorded Plat I of No. 5. Private Claims

SECTION

I, Keith R. Waters, in a field survey on October 30, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-7 1/4 Corner Common to Sections 14 & 23, T44N, R1W.

1845 - Original corner established by James H. Mullett. Witnesses: Fir 8, S57°W 14 links - Fir 6, N47°W 07 links.

ENOVUMEN "MINING Witnesses: Fir 8, S57°W 14 links – Fir 6, N47°W 07 links.

1921 – Chippewa County Surveyor Frederick H. Brown, RLS 944. Drawing of Section 23 shows the north line with the county Surveyor Frederick H. Brown, RLS 944. a distance of 5280 feet. The notes indicate that the ¼ corner is gone.

1993 - Keith R. Waters, P.S. 33142, Certificate of Survey, Liber 617, page 322, Chippewa County Records. Corner is shown as a set 3/4" iron midway on line between section corners 2640 feet east and west, no witnesses.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being reestablished as part of the Chippewa County Remonumentation Program. Found no evidence of the corner (it was never set in the above mentioned 1993 Survey). Set the corner midway on line between section corners at I-7 to the west and K-7 to the east as shown on said 1993 Certificate of Survey. Corner falls in the center of an east-west 2 track road and is 33'± south of the remains of an old east-west right-of-way fence on the north side of the old road. Placed a 3/2" rebar with plastic Chippewa County Remonumentation cap and established witness objects.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Placed a ¾" x 24" rebar with a plastic Chippewa County Remonumentation cap at the corner location, which falls in the center of an east-west 2 track road.

Witnesses:

Nail and plastic witness tag #33142 in blazed 9" Spruce, S66°W 29.28' Nail and plastic witness tag #33142 in blazed 4" Tamarack, N47°W 34.72' Nail and plastic witness tag #33142 in blazed 12" Tamarack, N41°E 16.42' Nail and plastic witness tag #33142 in blazed 6" Spruce, S06°W 7.38"

SINTE OF MICHIGAD KEITH B WATERS X. **PROFESSIONAL** A STATE OF ESCIONAL

Signed by Keith R. Warn

Date 12-29-00

Surveyor's Michigan License No. 33142