LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner

For corners in

ION
IC) F %

\$7.00 LAND CORNER

\$2,00 MSSR 2 FEB 2001 3:57:45 PM Receipt #1103 RECEIVED FOR RECORD

CHIPPENA COUNTY - STATE OF MICHIGAN SHARON H. KENNEDY, REGISTER OF DEEDS

PAGE 207 BOOK 11

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

SECTION

I, Keith R. Waters, in a field survey on November 6, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

9 10 30 29 28 11 12

2 3 4

5

6 18

7

8

A. Description of original monument and accessories and/or subsequent restoration:

L-3 1/4 Corner Common to Sections 1 & 12, T44N, R1W.

1845 - Original comer established by James H. Mullett. Witnesses: Cedar 8, N18°E 17 links - Birch 6, S52°W 13 links.

Found no evidence of subsequent restoration of this corner.



26

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being reestablished as part of the Chippewa County Remonumentation Program. Found no evidence of the original corner. Reestablished corner by single proportionate measurement on line between the section comer on the meridian at M-3 to the east and the section corner at K-3 to the west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner;

Placed a ¾" x 24" rebar with a stamped aluminum Chippewa County Remonumentation cap the corner location, which falls 100'± north of an east-west trail road.

Witnesses:

Nail and plastic witness tag #33142 in blazed 22" Hemlock, N51°W 25.83'

Nail and plastic witness tag #33142 in blazed 24" Hemlock, N04°E 25.72' Nail and plastic witness tag #33142 in blazed 24" Hemlock, N66°E 20.27'

Nail and plastic witness tag #33142 in blazed 26" White Pine, S05°W 45.22"



Date 12-29-00

Surveyor's Michigan License No. 33142

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED MAY 14, 1975
PAGE 207 REVISED OCT., 1995