

MAR 18 1999

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Chippewa County Remonumentation Corner #7.00 LAND CORNER

SECTION
For corners in

Chippewa County	Located in:	Corner Code #
1. Public Land Survey	T44N R2W	C-6
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No.	Recorded Plat	
5. Private Claims		

#2.00 MSSR

5 MAR 1999 10:50:06 AM Receipt #14013

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN
SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 10 PAGE 396

Register of Deeds Stamp & File Number

I, Keith R. Waters, in a field survey on November 20, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-6 1/4 Corner Common to Sections 17 & 18, Town 44 North, Range 2 West

1845 - Original corner (30" White Pine) established by James Mullett.

1897 - Sketch of Section 17 by Chippewa County Surveyor Frederick H. Brown, RLS 944, shows distances of 2640 feet on both the north and south 1/2 miles on the west side of said section.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being reestablished as part of the Chippewa County Remonumentation Program. Found no evidence of the original corner. Reestablished corner by single proportionate measurement on line between section corners at C-5 and C-7. Corner location falls on the approximate extension of remains of an old fence line to the west. The 1/2 mile distances are within 2 feet of those shown in the above mentioned County Surveyor notes.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Placed a 3/4" rebar with a plastic Chippewa County Remonumentation cap at the corner location, which falls approximately 3 feet west of the centerline of Mackinac Trail. Witnesses:

Nail and plastic witness tag #33142 in side of Power Pole (23/A), S15°E 295.41'
Nail and plastic witness tag #33142 in side of 6" Spruce, S28°E 272.38'
Nail and plastic witness tag #33142 in side of 6" White Pine, S68°W 130.48'
Nail and plastic witness tag #33142 in side of Power Pole (RU2/24), N70°W 99.65'

Signed by Keith R. Waters

Date 12-30-98

Surveyor's Michigan License No. 33142

BOOK 10 PAGE 396