

MAR 1 8 1999

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
Chippewa County Remonumentation Corner

For corners in SECTION

Chippewa County Located in: Corner Code #

1. Public Land Survey T44N R2W C-12
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

\$7.00 LAND CORNER
\$2.00 MSSR
5 MAR 1999 1:52:06 PM Receipt #14029
RECEIVED FOR RECORD
CHIPPEWA COUNTY - STATE OF MICHIGAN
SHARON H. KENNEDY, REGISTER OF DEEDS

BOOK 11 PAGE 2

Register of Deeds Stamp & File Number

I, Keith R. Waters, in a field survey on December 9, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-12 1/4 Corner Common to Sections 31 & 32. T44N, R2W

1845 - Original corner established by James Mullett.

Witnesses: Fir 8, S63°W 13 links - Tamarack 6, N62°E 15 links.

1906 - Chippewa County Surveyor Frederick H. Brown, RLS 944. Notes for Section 31 indicate that the east 1/4 corner of said section was made by McElvoy. Brown notes that McElvoy's post was gone, but McDonald had made a fence 2 rods west of McElvoy's corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found an old corner fence post with fences running north and west, as indicated in the above mentioned 1906 Brown notes. All evidence indicates that this fence corner is the point which Brown noted as being 2 rods west of the "McElvoy" corner. Although I do not believe that this "McElvoy" corner is a perpetuation of the original corner position, it has been used as the corner for probably in excess of 100 years. I established the corner 33 feet east of the found corner fence post, on the extension of the fence line to the west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner


Placed a 1/4" x 24" rebar with a stamped aluminum Chippewa County Remonumentation cap at the corner location, which falls 33 feet east of an old corner fence post. Witnesses:

Nail and plastic witness tag #33142 in side of blazed 8" Elm, S12°W 15.44'

Nail and plastic witness tag #33142 in side of blazed 4" Elm, N58°E 47.80'

Nail and plastic witness tag #33142 in side of blazed 3" Balsam Fir, N81°E 47.91'

Nail and plastic witness tag #33142 in side of blazed 6" Balsam Poplar, S65°E 36.94'



Signed by Keith R. Waters

Date 12-30-98

Surveyor's Michigan License No. 33142