

MAR 27 1996 CHIPPEWA COUNTY REMONUMENTATION CORNER

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T44N R 2W

T43N R 2W

T R

T R

S T R

S T R

S T R

S T R

G-13 Same
G-1 Corner

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

I, Keith R. Waters, in a field survey on 12/19, 1995 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-13 Corner Common to Sections 3 & 4, T43N, R2W & Sections 33 & 34, T44N, R2W

1840 - Corner established by William A. Burt was a 10" Aspen. Witnesses: Aspen 10, N10W° 08 links.

1845 - Witnesses added by James Mullett during the subdivision of T43N, R2W: Aspen 10, S47°E 19 links - Fir 4, S86°W 21 links.

1971 - Mary C. Feindt, P.S. 3920, as recorded in A-73, Mackinac County recorded corners. Placed "T" Iron by single proportionate measurement between recovered corners at S.W. corner of Section 33 and S.E. corner of Section 34, T44N, R2W.

1987 - Richard L. Hays, P.S. 25847, C-346 Mackinac County recorded corners. Set monument at position of found "T" iron above.

1987 - Richard L. Hays, P.S. 25847, D-21 Mackinac County recorded corners. Revised witnesses as shown in C-346 above.

1993 - David B. Guthrie, P.S. 22435, Mackinac County Remonumentation Surveyor, found monument as called for in D-21 above.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being perpetuated as part of the Chippewa County Remonumentation Program.

Found a 2 1/2" x 3' monument with a 3" aluminum cap stamped to identify the corner. Also found witness objects as called for in Mackinac County LCRC.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 2 1/2" x 3' monument with a stamped 3" aluminum cap. Witnesses:

8" Twin Ash, N68°W 49.84' Note: Trees are blazed and tagged.

6" Balsam Fir, S51°W 22.71' Distances are to nail blaze.

8" Balsam Fir, S70°E 17.33'

11" Balsam Fir, N52°E 20.38'

Steel Post, NORTH 2.70'

Signed by Keith R. Waters

Surveyor's Michigan License No. 33142

Date December 29, 1995

\$ 7.00 LAND CORNER

\$ 2.00 HSSR

28 FEB 96 4:33 P.M. RECEIPT# 459

RECEIVED FOR RECORD

CHIPPEWA COUNTY - STATE OF MICHIGAN

SHARON H. KENNEDY, REGISTER OF DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

