

Chippewa County Remonumentation Corner

RECEIVED FOR RECORD
CHIPPEWA COUNTY
STATE OF MICHIGAN

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

93 DEC 29 PM 2: 53

For corners in

Chippewa

(County)

Located In:

Corner Code #

J. Roger Malott

REGISTER OF DEEDS

1. Public Land Survey

T 44N R 3E

A-13/B-13 \ Same

T 43N R 3E

A-1/B-1 /Corner

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

SURVEY &
REMONUMENTATION

JUL 22 1999

Register of Deeds Stamp & File Number

SECTION

4. Lot No. , Recorded Plat

5. Private Claims

I, William L. Karr, in a field survey on December 16, 19 93

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A-13/B-13) Meander Corner Common to Section 31 (T44N-R3E) & Section 6 (T43N-R3E)

1840: Austin Burt, D.S.

White Ash 6 for Meander Corner.

Water from 1 to 3 feet deep.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A-13/B-13) This corner is being re-established as part of the Chippewa County Remonumentation Program.

Found no evidence of original corner. Re-established corner on the extension of the Township line at 432.96 feet (record GLO), East of Township Corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A-13/B-13) Corner is a 3/4" x 8' rod with "Chippewa County" stamped aluminum cap. Area is heavy, open marsh with standing water.

Witnesses:

Township Corner

N89°17'38"W 432.96'

South 1/4 Corner Section 36 (T44N-R2E)

N89°17'38"W 3072.96'

Concrete Monument

S88°43'37"W 663.09'

Fiberglass Rod

North 4.00'

Fiberglass Rod

South 4.00'



Signed by William L. Karr

Date 12/23/93

Surveyor's Michigan License No. 27450

NOTE: Bearings are compass bearings corrected for declination.

Distances are to a nail in side of witness objects unless noted.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1993

L.8 pg. 201 OTHER CODE : 1