

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Chippewa

(County)

Located In:

Corner Code #

1. Public Land Survey

T R

T R

T R

S T R

2. Property Controlling
in Section

S 26 T 45N R 1W

S 26 T 45N R 1W

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Mar 01 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(1-Sec. 26) West 1/16 corner between Sections 23 and 26. Not established in the original survey. Ronald Bishcer PS22428 established the corner in 2001. No record of witnesses.

(10-Sec. 26) South 1/16 corner between Sections 26 and 27. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(1-Sec. 26) Found a 1/2" iron pin with cap #22428 midway and on line between Section corner to West and Quarter corner to East. Accepted same as a careful and faithful determination of the position of the corner.

(10-Sec. 26) Established the corner midway and on line between Quarter corner 1323.26' North and Section corner 1323.26' South.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(1) Found 1/2" I. pin with plastic cap #22428. Set measuring nails in:

12" Cedar N27W 32.05' mrkd "W1/16 BT"

7" triple Maple N66W 5.2' do

5" Balsam N72E 3.5' do

4" Balsam S52E 2.45' do

Bearings are magnetic. Distances are to nail with tag. A N-S trail is 30' east.

(10) Set 1"IDx36" I. pipe with plastic cap stamped "MICH DNR PS33986". Set measuring nails in:

10" W.Birch N15W 17.75' mrkd "S1/16 BT"

12" Maple N38E 23.45' do

5" Balsam S79E 21.9' do

5" twin W.Birch S85W 28.65' do

Center of trail NW is 4' East.

Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski

Date

6/1/05

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

Revised May 14, 1975

Revised Jan., 1983

Revised Oct., 1999